

ENMAR -- YELLOW 23538,ALKYD ENAMEL;745-308 -- 8010-00-297-0585

=====
Product Identification
=====

Product ID:YELLOW 23538,ALKYD ENAMEL;745-308

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0585

MSDS Number: BDVZY

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL C

OATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RE

SPT TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE:IRRIT

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYE W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:85F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES:SCO*2,DRY CHEM. LG FIRES:POLYMER F OAM

PREFERRED

Fire Fighting Procedures:USE SELF-CONTAINED BREATING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MA EXPLODE DUE TO PRESSURE BUILD-UP

=====
Accidental Release Measures
=====

Spill Release Procedures:REOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE W/INERT ABSRBENT & NON-SPARKING TOOLS.

=====
Hand
ling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LG QTY IN BLDG DESIGNED TO STORE NFPACLASS ONE FLAM LIQ DO NOT TAKE INTERNALLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTANERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VETILATION. DOT:FLAM LIQUID.

=====
Exposure Controls/Personal Protection
=====

Re

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE
Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV
FUME

Protective Gloves:YES

Eye Protection:YES, FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

THIS PRODUCT IS A SEMI-GLOSS ENAMEL. VAPOR PRESSURE:3.2;VAPOR
DENSITY:HEAVIER THAN AIR;WT PER GALLON 10.78 LBS

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:

B.P. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:59.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN
ACCORDANCE W/FED.,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this
information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.