

PRATT & LAMBERT - WICHITA DIVISION -- 744-102 -- 8010-00-297-0809

=====
Product Identification
=====

Product ID:744-102

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0809

MSDS Number: BDWCW

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIVISION

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRA

TT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC NAPHTHA

Fraction by Wt: 8.0%

ACGIH TLV:200 PPM

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 15%.-

OSHA PEL:100 PPM

ACGIH

TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 8.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA
RTECS #:SE7525000
Fraction by Wt: 15.0%
ACGIH TLV:200 PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 0.04%
OSHA PEL:100 PPM

=====
===== Hazards Identification =====
=====

Effects of Overexposure:INH: ANESTHETIC, IRRITATE AIRWAY. SKIN/EYE
IRRITATION. HDACHE, DIZZINESS, COMA, CONFUSION

=====
===== First Aid Measures =====
=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES W/PLENT OF WATER.
REMOVE CONTAM CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL MD
IF SYMPTOMS PERSIST. ART RESP IF BRTHNG STOPS

=====
===== Fire Fighting Measures =====
=====

Flash Point:13F,-11C TCC
Lower Limits:0.

Extinguishing Media: CARBON DIOXIDE/ DRY CHEMICAL- SMALL. POLYMER FOAM LG
FIRE

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR
FIREMEN

Unusual Fire/Explosion Hazard: PRESSURE BUILD UP FROM EXTREME HEAT MAY
CAUSE EXPLOSION. USE WATER TO COOL CANS. FOR FIRE: FOG NOZZLE

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LG
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA
CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions: DO NOT TAKE INTERNALLY, CONTAINERS SHOULD BE GROUNDED
WHEN POURING. AVOID FREE FALL IN EXCESS OF A FEW INCHES. DO NOT
FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection: APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER
FILTER OR HOOD

Ventilation: GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY& WELDING

Protective Gloves: A LOT OF CONTACT

Eye Protection: USE EYEWEAR IF SPLASHING

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED
CLOTHING

Supplemental Safety and Health

BOILING RANGE 89-143°C

===== Physical/Chemical Properties =====

HCC: F3

Boiling Pt: B.P. Text: 193-290°F

Evaporation Rate & Reference: