

PRATT AND LAMBERT INC -- 743-720 -- 8010-00-297-2111

=====  
Product Identification  
=====

Product ID:743-720  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-297-2111  
MSDS Number: BDWFK  
=== Responsible Party ===  
Company Name:PRATT AND LAMBERT INC  
Address:945 BURLINGTON  
Box:206  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
Emergency Phone Num:316-733-1361  
CAGE:92216  
=== Contractor Identification ===  
Company Name:PRATT AND LAMBERT INC  
Address:945 BURLINGTON  
Box:206  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPHTHA  
RTECS #:SE7525000  
Fraction by Wt: 35,9%  
ACGIH TLV:200 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 8.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)  
CAS:6

7-56-1  
RTECS #:PC1400000  
Fraction by Wt: < 5%  
OSHA PEL:S,200PPM/250STEL  
ACGIH TLV:S,200PPM/250STEL; 93  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
Fraction by Wt: < 5%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TRIETHYLAMINE (SARA III)  
CAS:121-44-8  
RTECS #:YE0175000  
Fraction by Wt: 0.4%  
OSHA PEL:25 PPM/15 STEL  
ACGIH TLV:10 PPM/15 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5  
000 LBS

===== Hazards Identification =====

Effects of Overexposure:INHALED-ANESTHETIC, IRRITATE AIRWAY; SKIN/EYE IRRITATION HEADACHE, DIZZINESS, COMA, CONFUSION.

===== First Aid Measures =====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTONS PERSIST. PERFORM ARTIFICIAL RESPIRATION IF BR EATHING HAS STOPPED.

===== Fire Fighting Measures =====

Flash Point:44 F, 7 C TCC  
Lower Limits:0.9  
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER FOAM-LARGE FIRE  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMEN  
Unusual Fire/Explosion Hazard:PRESSURE BUILDUP FROM EXTREME HEAT MAY CAUSE EXPLOSION. USE WATER TO COOL CANS; FOR FIRE;FOGNOZZLES

===== Accidental Release Measures =====

=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Oth

er Precautions:DO NOT TAKE INTERNALLY, CONTAINERS SHOULD BE GROUNDED WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT FLAME CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF S PLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING, RANGE 106-143 C. ALSO CONTAINS CELLSOLVC ACETATE < 0.5 % AND MINERAL SPIRITS < 0.5 %.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:223-290 F

Evaporation Rate & Reference:< ETHER

Appearance and Odor:WHITE PAINT

Percent Volatiles by Volume:66.0

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: FIRES, HEAT, & HOT SURFACES, SPARKS,  
ELECTRICAL EQUIPMENT

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND  
FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.