

PANG RUBBER COMPANY -- BUFSOL-CODES:820,832,840,974,978 -- 2640-00-403-5539

=====
Product Identification
=====

Product ID:BUFSOL-CODES:820,832,840,974,978

MSDS Date:01/01/1987

FSC:2640

NIIN:00-403-5539

MSDS Number: BDXTN

=== Responsible Party ===

Company Name:PANG RUBBER COMPANY

Address:1650 NAUD ST

Box:2475

City:LOS ANGELES

State:CA

ZIP:90051

Country:US

CAGE:KO198

=== Contractor Identification ==

=

Company Name:PANG RUBBER CO

Address:1650 NAUD ST

Box:2475

City:LOS ANGELES

State:CA

ZIP:90051

Country:US

CAGE:0AES8

Company Name:PANG RUBBER COMPANY

Address:1650 NAUD ST

Box:2475

City:LOS ANGELES

State:CA

ZIP:90051

Country:US

CAGE:KO198

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 95%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450ST

EL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:STABILIZERS(ADDITIVES)

===== Hazards Identification =====

Effects of Overexposure:INH:ANAESTH.AT
1000PPM;DEATH;EXCESSIV.EXPOSURE:DAMAGE TO CARDIOVASCULAR,CENTRAL
NERVOUS SYSTEM.

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF
WATER. SKIN:WASH
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE
Autoignition Temp:Autoignition Temp Text:998F
Lower Limits:8
Upper Limits:10.5
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:AVOID OPEN FLAME,WELDING ARC
,OTHER HI
TEMP.WHICH CAUSE THERMAL DECOMP-AUTO IGN.TEMP.998F-

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER SAFETY EQUIPM-SM LEAKS:MOP UP
IMM,REMOVE TO OPEN AREA.ALLOW PROD.TO EVAPORATE-LG SPILLS:EVACUATE
AREA,CONTAIN LIQ.BY DIKING.TRANSFER TO CLOSED METAL CONT.KEEP OUT
OF WATER SUPPLY,SEWERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VEN

TED LOW FIRE

RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION. KEEP CONTAINERS
CLOSED.DON'T USE AL FOR PCKG/STG-NO MOISTURE-

Other Precautions:AVOID BREATHING VAPORS-VAP.IS HEAVIER THAN AIR AND
WILL COLLECT IN LOW AREAS.DO NOT ENTER THESE AREAS W/O SCBA AND AN
OBSERVER FOR ASSISTANCE.DO NOT SMOKE IN PRESENCE OF VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA OR FULL FACE RESP.IF TLV IS EXCEEDED.

Ventilation:PROVIDE MECHAN(GEN/L
OCAL EXHAUST)VENT TO MAINTN