View NSN Online: https://aerobasegroup.com/nsn/8010-00-437-6757

Product ID:MIL-P-24441/1,FORM 150,GREEN,COMP B MSDS Date:01/01/1985 FSC:8010 NIIN:00-437-6757 MSDS Number: BDYXJ === Responsible Party === Company Name: MOBIL CHEMICAL Address: HWY 27 Box:250 City:EDISON State:NJ ZIP:08818 Country:US CAGE:HO103 === Contractor Identification === **Company Name:** MOBIL CHEMICAL Address: HWY 27 Box:250 City:EDISON State:NJ ZIP:08818 Country:US CAGE:HO103 Company Name: MOBIL CHEMICAL CO DIV OF MOBIL OIL CORP Address: HWY 27 Box:250 City:EDISON State:NJ ZIP:08818 Country:US CAGE:29430 

Ingred Name:EPOXY RESIN Fraction by Wt: 50%

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:DE3030000 Fraction by Wt: 25% OSHA PEL:100 PPM

================== Hazards Identification

## Effects of Overexposure:EYE/SKIN:IRRITATION.VAPORS:RESP TRACT IRRITATION,DIZZINESS,NAUSEA,LOSS OF CONSCIOUSNESS.

## First Aid:EYE:FLUSH WITH WATER 15 MIN.SKIN:WASH WITH SOAP AND WATER.INHALATION:REMOVE FROM EXPOSURE.GIVE ARTIF RESP IF NEEDED,GET MEDICAL ATTN.

Flash Point:107F/41C (TCCPM) Lower Limits:0.7 Upper Limits:6 Ext inguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM,WATER FOG Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED CONTAINERS.

Spill Release Procedures: VENTILATE AREA. SECURE SOURCES OF IGNITION. AVOID BREATHING VAPORS AND PERSONAL CONTACT. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP.

Handling and Storage Precautions:DO NOT STORE ABOVE 120F/48C.KEEP AWAY FROM SPARKS,HEAT AND FLAMES.GROUND CONTAINER WHEN POURING,AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WIT EXPOSURE OF CONCERN. Ventilation:SPRAY BOOTH/LOCAL/MECHANICAL WITH EXPLOSION PROOF MOTORS. Protective Gloves:NEOPRENE Eye Protection:CHEM GOGGLE Othe r Protective Equipment:NEOPRENE/PLASTIC APRON.PROTECTIVE CLOTHING. Supplemental Safety and Health PART B OF 2 PART KIT.CONTAINER SIZE:5 GAL.KEY1:F4.

HCC:F4 Boiling Pt:B.P. Text:315F/157C Vapor Pres:3 Vapor Density:4 Spec Gravity:1.20 Evaporation Rate & amp; Reference:0.16 Solubility in Water:NEGLIGIBLE Appearance and Odor:NORMAL FOR A PAINT OR COATING TYPE PRODUCT Percent Volatiles by Volume:35

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE

Waste Disposal Methods:DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for

use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.