View NSN Online: https://aerobasegroup.com/nsn/8030-00-476-5299

Product ID:RTV88

MSDS Date:01/08/1986

FSC:8030

NIIN:00-476-5299

MSDS Number: BDZSZ === Responsible Party ===

Company Name: GENERAL ELECTRIC CO.; SILICONE PRODUCTS DIVISION

City:WATERFORD

State:NY ZIP:12188

Info Phone Num:(518)237-3330

Emergency Phone Num:(518)237-3330

CAGE:01139 === Contr

actor Identification ===

Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY ZIP:12188 Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL SILICATE

CAS:78-10-4

RTECS #: VV9450000

Fraction by Wt: 1000(RAT)MG/KG;INHAL(SUP DAT)

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVERE

XPOSURE SECTION.

Explanation of Carcinogenicity: NOT APPLICABLE

Effects of Overexposure:ACUTE:INGESTION-MAY CAUSE STOMACH DISCOMFORT. SKIN-PLANT EXPERIENCE HAS SHOWN THAT SKIN HAZARD IS NOT APPLICABLE IN THIS FORM. INHALATION-NONE KNOWN. EYE-MAY CAUSE MILD EYE IRRITATION. CHRONIC:LIVER & KIDNEY DAMAGE.

Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:EYE:IMME FLUSH W/LGE AMTS OF WTR FOR AT LEAST 15

MIN & GET

MED ATTN IF IRRI PERSISTS.INGES:IF SWALLOWED DO NOT INDUCE VOMITING, GIVE LGE QUAN OF WTR TO DRINK & GET MED ATTN, NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN:WASH W/SOAP & WTR. INHALATION:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTIFICIAL RESPIRATION)).

<i>"</i>
======================================
Flash Point Method:PMCC Flash Point:>200F/>93C Lower Limits:N/APPLICABLE Upper Limits:N/APPLICABLE Extinguishing Media:A LL STANDARD FIREFIGHTING MEDIA. Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT Unusual Fire/Explosion Hazard:N/K
========= Accidental Release Measures =========
Spill Release Procedures:WIPE,SCRAPE/SOAK UP IN AN INERT MATL & PUT IN A CONTAINR FOR DISPOSAL.WASH WALKING SURFACES W/DETERGENT & WTR TO REDUCE SLIPPING HAZARD.WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION.  Neutralizing Agent: N/K
============= Handling and Storage =============
Handling and Storage Precautions:AVOID CONTACT W/SKIN & EYES. USE ONLY IN A WELL VENTILATED AREA. CAUTION! Other Precautions:EYEWASH STATIONS. USE IN A WELL VENTILATED AREA.
====== Exposure Controls/Personal Protection ========

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation: USE ONLY IN WELL VENTILATED AREA.

Protective Gloves:CLOTH GLOVES.

Eye

Protection:SAFETY GLASSES.

Other Protective Equipment: EYEWASH STATIONS.

Work Hygienic Practices: N/K Supplemental Safety and Health

LD50:LC50MIX:LC50:>1000PPM/4HR(RAT).RTE ENTRY:

======== Physical/Chemical Properties =========

HCC:N1

Boiling Pt:B.P. Text:>500F/>260C

Melt/Freeze Pt:M.P/F.P Text:N/APPLICABL

Decomp Temp:Decomp Text:N/K

Vapor Pres:NEGLIGIBLE Vapor Density:NEGLIGIBLE

Spec Gravity:1.50

pH:N/APPL

Evaporation Rate & Properties Reference: NEGLIGIBLE

Solubility in Water:IN

SOLUBLE

Appearance and Odor:N/K Percent Volatiles by Volume: