

A.B.DICK CO. -- TONER CONCENTRATE 92-2185 (KIT P/N 92-2085) -- 6850-00-498-2345

===== Product Identification =====

Product ID:TONER CONCENTRATE 92-2185 (KIT P/N 92-2085)

MSDS Date:01/01/1987

FSC:6850

NIIN:00-498-2345

Kit Part:Y

MSDS Number: BFBMR

=== Responsible Party ===

Company Name:A.B.DICK CO.

Address:5700 WEST TOUHY AVENUE

City:CHICAGO

State:IL

ZIP:60648-4606

Country:US

Info Phone Num:312-547

-8800

Emergency Phone Num:312-647-8800

CAGE:HO951

=== Contractor Identification ===

Company Name:DICK A B CO

Address:7400 CALDWELL AVE

Box:City:NILES

State:IL

ZIP:60714-4628

Country:US

Phone:847-779-1900

CAGE:17638

Company Name:DICK A B CO

Address:5700 WEST TOUHY AVENUE

Box:City:CHICAGO

State:IL

ZIP:60648

Country:US

Phone:312-647-8800

CAGE:HO951

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON(MIXTURE OF C*9,C*10,C*11;% WT RANGE
OF MIXT

URE=50-60%
Fraction by Wt: 55.0%
ACGIH TLV:300 PPM(PER MFR

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 2.0%
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:POLYACRYLATE POLYMER;% WT RANGE 1-5%
Fraction by Wt: 3.0%

Ingred Name:PETROLEUM OIL % WT RANGE 5-10%
Fraction by Wt: 7.5%

Ingred Name:ROSIN DERIVATIVE;% WT RANGE:25-35%;(SEE SUPPL DATA FOR
BALANCE OF INGREDIENTS)
Fraction by Wt: 30.0%

=====
===== Hazards Identification =====
=====

Effects of Overexposure:DIZZINESS & HEADACHE.

=====
===== First Aid Measures =====

First Aid:INHALE: RMV TO FRESH AIR. IF NOT BRTHG GIVE CPR. IF BRTHG
DIFFICULT GIVE OXYGEN. INGEST: DO NOT INDUCE VOMITING. CONTACT:
IMMED FLUSH EYES OR SKIN W/ PLENTY OF WATER. RMV CONTAM CLTHG &
SHOES. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:106F-TCC
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. WIPE UP WITH DRY
RAGS OR COMMERCIAL ABSORBENT

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HANDLE OR STORE NEAR
HEAT,SPARKS,FLAME,OR STRONG OXIDANTS.
Other Precautions:NONE KNOWN

=====
===== Exposure Control

s/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACCEPTABLE.
Protective Gloves:AS REQUIRED
Eye Protection:OPTIONAL
Supplemental Safety and Health
BAL.OF INGRED:350F
Vapor Pres:UNK
Vapor Density:>1.0
Spec Gravity:0.866
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID,SLIGHT KEROSENE ODOR.
Percent Volatiles by Volume:50%

===== Stability and Reactivity Data =====

Stabil
ity Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL
Stability Condition to Avoid:HEAT, IGNITION SOURCES.CONCENTRATION OF
VAPORS.
Hazardous Decomposition Products:CO*2,CO,FUMES,SMOKE,ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISOPOSE OF COLLECTED WASTE MATERIAL IN
ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formul
ated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.