View NSN Online: https://aerobasegroup.ae/nsn/6850-00-498-2345

Product ID:TONER CONCENTRATE 92-2185 (KIT P/N 92-2085)

MSDS Date:01/01/1987

FSC:6850

NIIN:00-498-2345

Kit Part:Y

MSDS Number: BFBMR === Responsible Party === Company Name:A.B.DICK CO.

Address:5700 WEST TOUHY AVENUE

City:CHICAGO

State:IL

ZIP:60648-4606

Country:US

Info Phone Num:312-547

-8800

Emergency Phone Num:312-647-8800

CAGE:HO951

=== Contractor Identification === Company Name:DICK A B CO Address:7400 CALDWELL AVE

Box:City:NILES

State:IL

ZIP:60714-4628

Country:US

Phone:847-779-1900

CAGE:17638

Company Name: DICK A B CO

Address:5700 WEST TOUHY AVENUE

Box:City:CHICAGO

State:IL ZIP:60648 Country:US

Phone:312-647-8800

CAGE:HO951

====== Composition/Information on Ingredients ========

Ingred Name:PETROLEUM HYDROCARBON(MIXTURE OF C*9,C*10,C*11;% WT RANGE OF MIXT

URE=50-60% Fraction by Wt: 55.0% ACGIH TLV:300 PPM(PER MFR Ingred Name: CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 2.0% OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192 Ingred Name: POLYACRYLATE POLYMER; WT RANGE 1-5% Fraction by Wt: 3.0% Ingred Name: PETROLEUM OIL % WT RANGE 5-10% Fraction by Wt: 7.5% Ingred Name: ROSIN DERIVATIVE; WT RANGE: 25-35%; (SEE SUPPL DATA FOR BALANCE OF INGREDIENTS) Fraction by Wt: 30.0% ========== Hazards Identification ========== Effects of Overexposure:DIZZINESS & HEADACHE. First Aid: INHALE: RMV TO FRESH AIR. IF NOT BRTHG GIVE CPR. IF BRTHG DIFFICULT GIVE OXYGEN. INGEST: DO NOT INDUCE VOMITING. CONTACT: IMMED FLUSH EYES OR SKIN W/ PLENTY OF WATER. RMV CONTAM CLTHG & SHOES. CALL A PHYSICIAN. Flash Point: 106F-TCC Lower Limits:0.8 Upper Limits:7.0 Extinguishing M edia:CO*2, FOAM, DRY CHEM. Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ============ Spill Release Procedures: REMOVE ALL IGNITION SOURCES. WIPE UP WITH DRY RAGS OR COMMERCIAL ABSORBENT ============= Handling and Storage ========================== Handling and Storage Precautions: DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS. Other Precautions: NONE KNOWN

====== Exposure Control

s/Personal Protection =======
Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACEPTABLE. Protective Gloves:AS REQUIRED Eye Protection:OPTIONAL Supplemental Safety and Health BAL.OF INGRED:350F Vapor Pres:UNK Vapor Density:>1.0 Spec Gravity:0.866 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK LIQUID,SLIGHT KEROSENE ODOR. Percent Volatiles by Volume:50%
======== Stability and Reactivity Data =========
Stabil ity Indicator/Materials to Avoid:YES OXIDIZING MATERIAL Stability Condition to Avoid:HEAT, IGNITION SOURCES.CONCENTRATION OF VAPORS. Hazardous Decomposition Products:CO*2,CO,FUMES,SMOKE,ETC.
======= Disposal Considerations ==========
Waste Disposal Methods:DISOPOSE OF COLLECTED WASTE MATERIAL IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, & FEDERAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formul ated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

Disclaimer (provided with this information by the compiling agencies): This information is formul ated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.