

CORONADO PAINT CO., INC. -- TT-E-487,FLOOR & DECR GRAY,ENAMEL,OIL -- 8010-00-527-0217
===== Product Identification =====

Product ID:TT-E-487,FLOOR & DECR GRAY,ENAMEL,OIL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-0217

MSDS Number: BFCPY

=== Responsible Party ===

Company Name:CORONADO PAINT CO., INC.

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== C

Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

===== Composition/Information on Ingredients =====

Ingred Name:PIGMENTS

Fraction by Wt: 46.3%

Ingred Name:ALKYD RESIN

Fraction by Wt: 26.8%

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 26.9%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 899

===== Hazards Identification =====

Effects of Overexposure:EYES: SEVERE IRRIT. SKIN: DRYING. INH:
EXCESSIVE-HEADACHE, DIZZINESS, NAUSEA.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER. SKIN: WASH W/MILD SOAP & WATER, APPLY
SKIN CREME. INHAL: REMOVE TO FRESH AIR, CALL MD. APPLY ART RESP IF
NECESSARY.

===== Fire Fighting Measures =====

Flash Point:102F SETA
Low
er Limits:0.8
Upper Limits:5.0
Extinguishing Media:FOAM, CO*2, DRY CHEMICAL
Fire Fighting Procedures:TREAT AS CLASS B FIRE
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES W/AIR

===== Accidental Release Measures =====

Spill Release Procedures:WEAR A RESPIRATOR.FLUSH W/WATER INTO RETAINING
AREA OR CONTAINER.AVOID EXPOSURE TO SPARKS,FIRE OR HOT METAL
SURFACES.

===== Handling and Storage =====

Handling and St
orage Precautions:KEEP AWAY FROM HEAT,SPARKS, & OPEN
FLAME. USE W/ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED SKIN
CONTACT.
Other Precautions:DOT: COMBUSTIBLE LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED,APPROVED RESPIRATOR IF TLV IS
EXCEEDED.
Ventilation:USE LOCAL EXHAUST
Protective Gloves:YES
Eye Protection:YES
Other Protective Equipment:EYE BATH & SAFETY SHOWER
Supplemental Safety and Health
VAPOR PRESS: <

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315F
Vapor Density:4.90
Spec Gravity:1.3800
Evaporation Rate & Reference:0.1 N-BUAC
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GRAY OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR
Percent Volatiles by Volume:44.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STONG OXIDIZERS
Stability Condition to Avoid:EXCESSIVE HEAT,SPARK
S, & OPEN FLAMES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATION IF IN ACCORDANCE WITH
FED,STATE AND LOCAL CODES (MFG REC)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expre
ssly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.