

NORRIS PAINT COMPANY -- 34072-GREEN -- 8010-00-527-2407

=====
Product Identification
=====

Product ID:34072-GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2407

MSDS Number: BFCRL

=== Responsible Party ===

Company Name:NORRIS PAINT COMPANY

Emergency Phone Num:503-364-2277

CAGE:JO883

=== Contractor Identification ===

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST

NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

Company Name:NORRIS PAINT COMPANY

Box:2023

CAGE:JO883

=====
Composition/Information on Ingredients
=====

Ingred Name:PIGMENT

Fraction by Wt: 38%

Ingred Name:VEHICLE

Fraction by Wt: 12%

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2.4%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:WATER

CAS:7732-18-5

RT

ECS #:ZC0110000
Fraction by Wt: 45.6%

Ingred Name:ADDITIVE
Fraction by Wt: 2.0%

=====
Hazards Identification
=====

Effects of Overexposure:SLIGHT NAUSEA IF INGESTED

=====
First Aid Measures
=====

First Aid:INGESTION- INDUCE VOMITING- GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:NA
Fire Fighting Procedures:NA
Unusual Fire/Explosion Hazard:NA

=====
Accidental Release Measures
=====

Spill Release Procedures:SMALL SPILLS MAY BE FLUSHED DOWN DRAIN, OR
DISPOSED OF IN LANDFILL ACCORDING TO LOCAL REG.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT FREEZE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:APPROVED DUST MASK WHEN SPRAY PAINTING
Ventilation:NONE
Protective Gloves:NONE
Eye Protection:
NONE
Other Protective Equipment:NONE
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:N1
Boiling Pt:B.P. Text:212F, 100C
Vapor Pres:24
Spec Gravity:1.38
Evaporation Rate & Reference:0.36 BUAC
Solubility in Water:COMPLETE
Appearance and Odor:OPAQUE LIQUID / SLIGHT ODOR.
Percent Volatiles by Volume:66

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
OIL BASED MATERIALS- PETR

OLEUM DISTILLATES

Stability Condition to Avoid:EXTREME HEAT OVER 212F

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.