

PRATT & LAMBERT- WICHITA DIVISION -- 793-310 -- 8010-00-527-2624

===== Product Identification =====

Product ID:793-310
MSDS Date:01/01/1985
FSC:8010
NIIN:00-527-2624
MSDS Number: BFCVL
=== Responsible Party ===
Company Name:PRATT & LAMBERT- WICHITA DIVISION
Address:945 BURLINGTON
Box:206
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
CAGE:KO010
=== Contractor Identification ===
Company Name:PRATT
& LAMBERT-WICHITA DIV.
Box:2153
CAGE:KO010
Company Name:PRATT AND LAMBERT INC
Address:945 BURLINGTON
Box:206
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE
RTECS #:IA4025000
Fraction by Wt: 35.0%
ACGIH TLV:150 PPM

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC NAPHTHA
RTECS #:SE7525000
Fraction by Wt: 8.0%
ACGIH TLV:200 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 15.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: < 5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRIT. TO AIRWAY; IRRIT.
SKIN/EYE: HEADACHE,DIZZY,COMA

===== First Aid Measures =====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED:REMOVE TO FRESH
AIR. CALL A DR. IF SYMPTONS PERSIST.

===== Fire Fighting Measures =====

Flash Point:13F,-11 C, T

CC

Lower Limits:0.9

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER
FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMAN

Unusual Fire/Explosion Hazard:CLOSED CONTANERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESURE BUILD-UP, USE H*2O TO COOL CLOSED CANS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, & ELECTRICAL, STATIC, OR
FRICTIONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS
ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED
WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW
INCHES, DO NOT
FLAME CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTIION/LOCAL EXHAUST FOR TLV&LEL SAFETY &
WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety a

nd Health

BOILING RANGE 79-143C ALSO CONTAINS ISOPROPYL ALCOHOL < 5%, VM&P
MAPHTHA