

OCTAGON PROCESS INC. -- PENETRATING OIL,VV-P-216 -- 9150-00-529-7518

=====  
Product Identification  
=====

Product ID: PENETRATING OIL,VV-P-216  
MSDS Date: 01/01/1987  
FSC: 9150  
NIIN: 00-529-7518  
MSDS Number: BFCZV  
==== Responsible Party ====  
Company Name: OCTAGON PROCESS INC.  
Address: 596-RIVER-ROAD  
City: EDGEWATER  
State: NJ  
ZIP: 07020  
Country: US  
Info Phone Num: 201-945-9400  
Emergency Phone Num: (201)945-9400  
C  
AGE: 82925

==== Contractor Identification ====  
Company Name: OCTAGON PROCESS INC.  
Address: 596 RIVER ROAD  
Box: City: EDGEWATER  
State: NJ  
ZIP: 07020  
Country: US  
Phone: 201-945-9400  
CAGE: 82925

=====  
Composition/Information on Ingredients  
=====

Ingred Name: PETROLEUM OIL,  
ACGIH TLV: 5 MG/CUM MIST

Ingred Name: PROPELLANT(TYPE EITHER HYDROCARBON OR CARBON DIOXIDE)

=====  
Hazards Identification  
=====

Health Hazards Acute and Chronic: NONE SPECIFIED BY MANUFACTU

RER.  
Effects of Overexposure:MAY IRRITATE EYES AND SKIN OR DERMATITIS ON CONTACT.  
INHAL:-CANCAUSE,HEADACHE,NAUSEA,VOMITING.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====  
===== Fire Fighting Measures =====

Flash Point:N/R-AEROSOL  
Lower Limits:0.7  
Upper Limits:5.0  
Extinguishing Media:FOAM,CO, DRY CHEMICAL  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:AEROSALS CANS MAY EXPLODE AT HIGH TEMP.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:TREAT AS OIL SPILL USE SUITABLE ABSORBENT TO RECOVER IT IN TO A CONTAINER.WASH DOWN THE SURFACE WITH WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE.USE ADEQUATE VENTILATION AND NORMAL PRECAUTION FOR HANDLING OIL SPILLS.  
Other Precautions:AVOID SKIN AND EYES CONTACT.DO NOT INHALE AN OIL MIST.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.  
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION  
Protective Gloves:RUB

BER  
Eye Protection:GOGGLES  
Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.  
Supplemental Safety and Health  
UNDATED MSDS RECD 22JUN84. SINCE PROPELLANT NOT SPECIFIED, WORST CASE  
ASSUMED, IE, FLAMMABLE.

===== Physical/Chemical Properties =====

HCC:V3  
Boiling Pt:B.P. Text:338-572F  
Vapor Density:4.5  
Spec Gravity:0.81  
Solubility in Water:INSOLUBLE  
Appearance and Odor:PALE YELLOW COLOR-OILY ODOR  
Percent Volatiles by Volume:UNKN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED  
Stability Condition to Avoid:NONE SPECIFIED  
Hazardous Decomposition Products:NONE SPECIFIED

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF THE COLLECTED MATERIAL IN ACCORDANCE  
WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use  
by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.