View NSN Online: https://aerobasegroup.com/nsn/8030-00-537-7925

Product ID:SCOTCHSEAL INDUSTRIAL SEALANT (3M EC 1063) MSDS Date:01/01/1985 FSC:8030 NIIN:00-537-7925 MSDS Number: BFDHW === Responsible Party === Company Name: 3M COMPANY, ADHESIVE COATING & SEALANT DIV. Address:3M CENTER City:ST. PAUL State:MN ZIP:55144-1000 Country:US Info Phone Num:612-733-1110 Emergency Phone Num:612-733-1110 CAGE:04963 === Contractor Identification === Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV Address:3M CTR Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:800-364-3577/651-737-6501(24 HOURS) CAGE:04963 Ingred Name: LEAD PEROXIDE (LEAD DIOXIDE), (OSHA PEL FROM 29CFR 1910.1025) CAS:1309-60-0 RTECS #:0G0700000 Fraction by Wt: 50%. OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.15 MG/M3(PB); 8990 Ingred Name: DIBUTYL PHTHALATE (SARA III) CAS:84-74-2 RTECS #:TI0875000 OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS Ingred Name:STEARIC ACID (COMBINED W/DIBUTYL PHTHALATE.COMPRISES APPROX. 50% OF PRODUCT) CAS:57-11-4 RTECS #:WI2800000

Effects of Overexposure: CHRONIC EXPOSURE CAN LEAD TO LEAD POISONING.

| SKIN CONTACT. | |
|---------------|--|
|---------------|--|

| ====================================== |
|--|
| First Aid:EYE: FLUSH W/ PLENTY OF WATER & CALL A PHYSICIAN. |
| ====================================== |
| Extinguishing Media:CO*2, FOAM, DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE |
| ====================================== |
| Spill Release Procedures:COLLECT SPILLED MATERIAL USING ABSORBENT MATERIAL. CLEAN UP RESIDUE & AREA |
| ====================================== |
| Handling and Storage Precautions: AVOID EYE CONTACT 6 PROLONGED SKIN CONTACT. WASH HANDS BEFORE EATING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. |
| ====================================== |
| Ventilation:MFR STATES: MECHANICAL VENTILATION ADEQUATE Protective Gloves:IMPERV. GLOVES Eye Protection:SAFETY GLASSES Supplemental Safety and Health SOLUBILITY IN WATER: VERY SLIGHT, THIS PRO DUCT CAN BE USED W/EC-801 (ADHESIVE). KEY1: J3. |
| ====================================== |
| HCC:D1 Spec Gravity:1.9 Appearance and Odor:DARK BROWN PASTE Percent Volatiles by Volume:0.0 |
| ====================================== |
| Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO, CO*2, & SMOKE PARTICLES |
| ====================================== |
| Waste Disposal Methods:MFR RECM: LG QTY- |

-DISPOSE IN SECURE LANDFILL AT

HAZARDOUS WASTE MANAGEMENT FACILITY. CONSULT APPROPRIATE FED., STATE & LOCAL CODES. SM QTY--DISPOSE OF INDIV EMPTY CONTAINERS IN A SANITARY LANDFILL IAW FED,. STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a nd

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.