View NSN Online: https://aerobasegroup.com/nsn/4730-00-542-3359

BONDED PRODUCTS,INCORP. -- EPI-SEAL UNIVERSAL RESIN,HARDNER,PART B

4730-00-542-3359

Product ID:EPI-SEAL UNIVERSAL RESIN, HARDNER, PART B

MSDS Date:01/01/1985

FSC:4730

NIIN:00-542-3359

Kit Part:Y

MSDS Number: BFDMD === Responsible Party ===

Company Name: BONDED PRODUCTS, INCORP.

Emergency Phone Num:215-696-9220

CAGE:DO082

=== Contractor Identification ===

Company

Name: BONDED PRODUCTS INCORPORATED (CANCELLED 19092 - NEW)

Address:439 S BOLMAR ST

Box:39

City:WEST CHESTER

State:PA

ZIP:19382-4933 Country:US

CAGE:3L885

Company Name:BONDED PRODUCTS, INC Address:439 SOUTH BOLMAR STREET

Box:39

City:WEST CHESTER

State:PA

ZIP:19381-0039

Phone:610-696-9220 OR 215-739-9960

CAGE:DO082

======= Composition/Information on Ingredients ========

Ingred Name: POLYAMINE (CATALYST, HARDNER)

Fraction by Wt: 89%

Ingred Name:FILLERS,UNSPECIFIED

Fraction by Wt: 11%

| ============ Hazards Identification ============= |
|---|
| Effects of Overexposure:VAPORS CAUSE SKIN/EYE BURNS,MAY CAUSE NAUSEA,VOMITING & BE IRRITATING.MAY CAUSE SKIN RASH. |
| ====================================== |
| First Aid:EYES/SKIN-FLUSH WITH WATER FOR AT LEAST 15 MINS.SKIN-WASH W/MILD SOAP & WATER.GIVE OXYGEN IF BREATHING DIFFICULT.REMOVE CONTAMINATED CLOTHES.CALL A DR. FOR ANY OF ABOVE EXPOSURES. |
| ====================================== |
| Flash Point:>250 F COC Lower Limits:1.0 Upper Limits:6.5 Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM,WATER SPRAY Fire Fighting Procedures:WEAR NIOSH SELF CONTAINED BREATHING GEAR.(SEE SUPP DATA) |
| Unusual Fire/Explosion Hazard:OXIDES OF NITROGEN & CARBON CAN BE EVOLVED.HANDLE PRODUCT AS COMBUSTIBLE MATERIAL. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures: ABSORB. SHOVEL INTO CONTAINERS FOR SAFE |
| SHIPMENT TO DISPOSAL AREA.WEAR PROTECTIVE CLOTHING & WORK IN WELL VENTILATED AREA.DISCARD HEAVILY SOILED CLOTHING. |
| ====================================== |
| Handling and Storage Precautions:STORE IN COOL AREA IN ORIGINAL CONTAINERS NOT OVER 90F. Other Precautions:USE WITH ADEQUATE VENTILATION.WASH THOROUGHLT AFTER HANDLING.CALL MD. IN EXTREME EMERGENCIES. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:AIR SUPPLIED OR S |

ELF CONTAINED NIOSH APPROVED MASKS

Ventilation:LOCAL REQUIRED TO DISSIPATE VAPORS

Protective Gloves:RUBBER

Eye Protection: SPLASH PROOF GOGG, W/SHIEL

Other Protective Equipment:IMPERVIOUS RUBBER GARMETS,SAFETY SPRAY OR SHOWER & EYE BATH

Supplemental Safety and Health

SPRAY WATER ON CONTAINERS EXPOSED TO FIRE.STAY UPWIND.ITEM IS ASSEMBLY 1 OF MIL-R-17882.KEY1:N1.

======== Physical/Chemical Properties ==========

HCC:N1

Boiling Pt:B.P. Text:>250 F

Vapor Density:4.0 Spec Gravity:1.0

Solubility in Water: VERY SLIGHT

Appearance and Odor:BLACK LIQUID WITH A SLIGHT CHARACTERISTIC ODOR

Percent Volatiles by Volume: