

CON-LUX COATINGS, INC. -- ALKYD,FLAT,WHITE 37875 -- 8010-00-550-5274

=====
Product Identification
=====

Product ID:ALKYD,FLAT,WHITE 37875

MSDS Date:01/01/1985

FSC:8010

NIIN:00-550-5274

MSDS Number: BFDWG

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Emergency Phone Num:201-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE R

D

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 31%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF EYES AND SKIN.IRRITATION OF
RESPIRATORY TRACT HEADACHE OR DIZZY.

=====
First Aid Measures
=====

=====
First Aid:SKIN/EYES: FLUSH WITH PLENTY OF WATER. INHAL:REMOVE TO FRESH AIR. IF IRRITATION PERSISTS,CALL DR.

=====
Fire Fighting Measures =====

Flash Point:50.6/123 CC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:USE CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEM.,FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND ISOLATE FROM SOURCES OF IGNITION.

=====
Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING VAPORS. VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====
Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP AWAY FROM OPEN FLAME AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM/MECH FILTER RESPIRATOR

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Supplemental Safety and Health CLOSE

D CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:174/346
Vapor Pres:4
Vapor Density:5.3
Spec Gravity:1.37
Evaporation Rate & Reference:BUAC=1: 0.05
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE LIQUID,MILD ALIPHATIC ODOR.
Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.