

D A P INC -- DAP BUTYL GUTTER & LAP SEALANT -- 8030-00-550-8628

=====  
Product Identification  
=====

Product ID:DAP BUTYL GUTTER & LAP SEALANT

MSDS Date:01/01/1987

FSC:8030

NIIN:00-550-8628

MSDS Number: BFDYF

=== Responsible Party ===

Company Name:D A P INC

Address:5300 HUBERVILLE ROAD

Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Info Phone Num:513-236-0911

Emergency Phone Num:513-236-0911

CAGE:IO869

=== Contractor Identification ===

Company Name:D A P INC

Box:277

City:DAYTON

State:OH

ZIP:45411-0277

Country:US

Phone:800-543-3840

CAGE:IO869

Company Name:DAP INC.

Address:Box:277

City:DAYTON

State:OH

ZIP:45401-0277

Country:US

Phone:513-253-7154/800-543-3840

CAGE:90300

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 1-10%

OSHA PEL:100 PPM

Ingred Name:VM & P NAPHTH

A CAS#8030-30-6  
RTECS #:QI9458000  
Fraction by Wt: 1-5%  
ACGIH TLV:300 PPM

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 0-2%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

===== Hazards Identification =====

Effects of Overexposure:ACUTE:LIQ,VAP IRRIT EYE,SKIN,RESPIR TRACT.MAY  
CAUSE CENTRAL NERV SYST DEPRESS:HDCH,DIZZ,FAT,NAUS.SUP

===== First Aid Measures =====

First Aid:INHAL:R  
EMOVE TO FRESH AIR.RESTORE BREATH IF NECESSARY.GET  
MD.EYE:FLUSH W/ LARGE AMONTS OF WATER FOR 15 MIN.CONTACT A  
PHYSICIAN.SKIN:WASH W/ SOAP & WATER.GET MD IF IRRIT  
DEVELOPS.INGEST;DO NOT INDUCE V OMIT.GIVE H\*20,MILK.CONTACT A MD  
IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point:58F,14C TCC  
Extinguishing Media:FOAM,CO\*2,DRY CHEMICALS  
Fire Fighting Procedures:COOL CONTNR W/ H\*20 DO NOT USE STRAIGHT HOSE  
STREAM.USE SCBA  
Unusual Fire/Exp  
losion Hazard:CONTNR MAY EXPLO IF EXPO TO EXTREME  
HEAT.ISOLATE FROM IGNIT SOURC.DO NOT PUT IN CONTACT W/ OXIDI HAT

===== Accidental Release Measures =====

Spill Release Procedures:LARGE:USE PROTECT EQUIP.ELIMINATE ALL SOURCES  
OF IGNIT,VENTILATE SPILL AREA.CONTAIN SPILL BY DIKING.ABSORB SPILL  
W/ ABSORBT MATRL.SHOVEL INTO CONTNR.CLEAN UP REMAINING W/ A NONFLAM  
SOLVENT:1,1,1-TRICH LOROETHANE.PREVENT RUN-OFF TO  
STREAM,SEWERS.SUPP

=====

=== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTNR FROM HEAT,FLAMES,DIRECT SUNLIGHT.DO NOT STORE AT TEMP ABOVE 120F.PROVIDE CROSS VENT IN STORAGE AREA.AVOID PRLG/RPTD BREATH,SKIN CONTACT

Other Precautions:KEEP CONTNR TIGHTLY CLOSED WHEN NOT IN USE.CONTAINS FLAMM SOLVENT.VAP HARMF,MAY CAUSE FLASH FIRE.HARM OR FATAL IF SWALLOWED.USE ONLY W/ ADEQUATE VENT & ELIMINATE SOURCES OF IGNITION.WASH CLOTH

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOS/MSHA APPROVD RESPIRATOR IF TLV EXCEEDED.  
Ventilation:MECHANICAL VENT(LOCAL OR GENERAL EXHAUST) TO KEEP BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGG W/ SIDE SHIELDS

Other Protective Equipment:EYE WAS & SOLVENT IMPERV APRON.BARRIER CREAM MAY BE USED

Supplemental Safety and Health

MSDS PREP:17MAY86.SPEC:TYPE 2,CLASS A.BP:100-200C.OVEREXPO:INGEST:CAUSE NAUSEA,VOMIT,DIARR,DEPRESS RESPIRATION.IN CASE OF SPILL:NOTIFY

LOCAL HEALTH OFFIC.SMALL:USE ABSORB MAT,PLACE INTO CONTNR

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:212-392F

Spec Gravity:1.46

Evaporation Rate & Reference:N/K(PER MFR)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE PASTE W/ A PETROLEUM DISTILLATE ODOR

Percent Volatiles by Volume:15.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS AND CAU

STICS

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:NORMAL CONBUSTION  
PRODUCTS,I.E.CO\*X,NO\*X

===== Disposal Considerations =====

Waste Disposal Methods:DISCARDED SPILL RESIDUE MAY BE INCINERATED.DO  
NOT INCINERATE SEALED CONTAINERS.DISPOSE ACCORDING TO FEDERAL,STATE  
AND LOCAL REGULATIONS.LIQUID CAN NOT BE DISPOSED OF IN A LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.