View NSN Online: https://aerobasegroup.com/nsn/8030-00-551-2801

3M COMPANY -- WEATHERBAN SEALANT 101 WHITE -- 8030-00-551-2801

Product ID:WEATHERBAN SEALANT 101 WHITE MSDS Date:01/01/1985 FSC:8030 NIIN:00-551-2801 MSDS Number: BFDZK === Responsible Party === Company Name:3M COMPANY Emergency Phone Num:612-733-2328 CAGE:76381 === Contractor Identification === Company Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV А ddress:3M CTR Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:800-364-3577/651-737-6501(24 HOURS) CAGE:04963 Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 3% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM ; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:BARIUM COMPOUND Fraction by Wt: 4% ACGIH TLV:0.5MG/CUM AS BA

==

Effects of Overexposure: POSSIBLE EYE/SKIN IRRITATION

First Aid:FLUSH EYES WITH H*20 FOR 15 MIN, CALL PHYSICIAN. WASH SKIN WITH SOAP & WATER.

Flash Point:SEE SUP P DATA Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:CO*2, FOAM, DRY CHEMICAL Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: COLLECT SPILLED MATERIAL & PLACE IN A CLOSED CONTAINER.

Other Precautions: AVOID EYE CONTACT & EXCESSIVE SKIN CONTACT. WASH HANDS THOROUGHLY BEFORE EATING OR SMOKING.

========

==== Exposure Controls/Personal Protection =========

Ventilation:MECHANICAL VENTILATION RECOMMENDED Eye Protection:SAFETY GLASSES Supplemental Safety and Health CONTAINER SIZE:12.8 OZ CARTRIDGE. BOILING POINT, VAPOR PRESSURE, LEL & UEL ARE FOR TOLUENE. FLASHPOINT-PRODUCT DOES NO YIELD A FLASH VIA CLOSED CUP. PERCENT VOLATILE BY WEIGHT IS 3.

HCC:N1 Boiling Pt:B.P. Text:230F;110C Vapor Pres:22 Vapor Density:>2 Sp ec Gravity:1.75 Evaporation Rate & Reference: