

CORONADO PAINT COMPANY, INC -- ENAMEL -- 8010-00-579-9201

=====  
Product Identification  
=====

Product ID:ENAMEL

MSDS Date:01/01/1985

FSC:8010

NIIN:00-579-9201

MSDS Number: BFGBW

=== Responsible Party ===

Company Name:CORONADO PAINT COMPANY, INC

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== Contractor Identification ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 26.9%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:SEVERE EYE IRRITATION.DRIES SKIN.INHALATION

C

# AUSES HEADACHE, DIZZINESS AND NAUSEA

## ===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER.SKIN-WASH WITH MILD SOAP AND WATER;APPLY SKIN CREAM.INHALATION-REMOVE TO FRESH AIR-CALL PHYSICIAN-APPLY ARTIFICIAL RESPIRATION IF NECESSARY

## ===== Fire Fighting Measures =====

Flash Point:102F;39C SCC  
Lower Limits:0.8  
Upper Limits:5.0  
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL  
Fire Fighting Procedures:TREA  
T AS CLASS B FIRE  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR

## ===== Accidental Release Measures =====

Spill Release Procedures:WEAR RESPIRATOR.FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER.AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES

## ===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE WITH ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED  
Ventilation:LOCAL  
Protective Gloves:YES  
Other Protective Equipment:EYE BATH AND SAFETY SHOWER  
Supplemental Safety and Health

## ===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:315F;152C  
Vapor Pres:80  
Vapor Density:4.9  
Spec Gravity:1.38  
Evaporation Rate &

amp; Reference:0.1 BUAC  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:GRAY OPAQUE LIQUID.PETROLEUM DISTILLATE ODOR  
Percent Volatiles by Volume:44.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:HEAT, SPARKS,OPEN FLAMES OR FIRE  
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED  
CONDITIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.