

SEAGRAVE COATING CORP CHEMRAY DIVISION -- F-120,MIL-P-L5930,VINYL CHROMATE PAINT --
8010-00-584-2953

===== Product Identification =====

Product ID:F-120,MIL-P-L5930,VINYL CHROMATE PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-584-2953

MSDS Number: BFGJY

=== Responsible Party ===

Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:

US

Info Phone Num:201-245-1111

Emergency Phone Num:201-245-1111

CAGE:8D124

=== Contractor Identification ===

Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:8D124

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rp

t Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TRICRESYL PHOSPHATE 8W/VINYL CHLORIDE-VINYLAACETATE
COPOLYMER THEY FORM 20% OF PRODUCT)

ACGIH TLV:0.1 MG/CUM

Ingred Name:VINYL CHLORIDE VINYL ACETATE COPOLYMER (W/TRICRESYL
PHOSPHATE THEY FORM 20% OF PRODUCT)

ACGIH TLV:0.1 MG/CUM

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

OSHA PEL:0.1 MG/M3

(CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

=====
Hazards Identification
=====

Effects of Overexposure:MAY IRRIT SKIN/RESP SYS. OVER INH MAY CAUSE
LOWERING OF BODY TEMP, HEAT/RESP RATE.

=====
First Aid Measures
=====

First Aid:FLUSH EXPOSED SKIN FREELY W/WATER, CALL MD IF NEC. IF OVER
INH OCCURS, REMOVE TO WELL-VENT AREA.

=====
Fire Fighting Measures
=====

Flash Point:45F TOC

Lower L

imits:1.2

Upper Limits:7.5

Extinguishing Media:DRY CHEM, CO*2

Fire Fighting Procedures:WATER SPRAY MAY BE INEFF AS EXTINGUISHING
AGENT

Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL GREAT DISTANCE & FLASH
BACK TO ORIGIN

=====
Accidental Release Measures
=====

Spill Release Procedures:FOLLOW GEN CLEANING PROCEDURES. SM SPILLS MAY
BE WASHED AWAY W/WATER, MFR REC.

=====
Handling and Storage
=====

Handling and Storage Pr

Precautions: STORE IN COOL, DRY PLACE AWAY FROM
OPEN FLAMES & PHYSICAL ABUSE & W/GOOD VENT.

Other Precautions: ODOR THRESHOLD NOT SUFFICIENT TO WARN OF DANGEROUS
CONC. SECURE ALL SOURCES OF IGNITION. KEEP CONTAINERS CLOSED AS MUCH AS
POSS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF-CONTAINED BREATHING APPARATUS, NIOSH/MSHA APPROVED

Ventilation: USE LOCAL & MECHANICAL EXHAUST

Protective Gloves: YES

Eye Protection: YES

Supplemental Safety and Health

LMPBLACK, M

G-S10*4 & ZN-CRO4 FORM 15% ALUMINUM STERATE