

PHIPPS PRODUCTS CORP -- XYLENE -- 6810-00-584-4071

=====
Product Identification
=====

Product ID:XYLENE
MSDS Date:01/01/1987
FSC:6810
NIIN:00-584-4071
MSDS Number: BFGQS
=== Responsible Party ===
Company Name:PHIPPS PRODUCTS CORP
Address:186 LINCOLN ST SUITE 502
City:BOSTON
State:MA
ZIP:02111-2403
Country:US
Emergency Phone Num:NONE
CAGE:86511

==== Contractor Identification ====

Company Name:PHIPPS
PRODUCTS CORP
Address:186 LINCOLN ST SUITE 502
Box:City:BOSTON
State:MA
ZIP:02111-2403
Country:US
Phone:OUT OF BUSINESS
CAGE:86511

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 100%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:

IRRITATING RESPIRATORY TRACT.MAY CAUSE
DIZZINESS,UNCONSCIOUSNESS,OR COMA.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point:28C/82F (T.C.C.)

Lower Limits:1.1

Extinguishin

g Media:DRY CHEMICAL,CO*2,FOAM.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA TO FIGHT FIRES.COOL
CNTNRS W.WATER

Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT AND OPEN FLAME.CLOSED
CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ISOLATE FROM SOURCE OF IGNITION.USE PERSONAL
PROTECTION EQUIPMENT.COLLECT LEAKING LIQUID IN A SEALABLE
CONTAINER,ABSORB SPILLED LIQUID IN SAND OR INER
T ABSORBENT AND
RECOVER IT FOR FURHTER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE
RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.
KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:USE ADEQUATE VENTILATION.AVOID BREATHING VAPORS AND
CONTACT WITH SKIN AND EYES.EMPTY CONTAINER HAZARDOUS.USE ALL
NECESSAY PRECAUTIONS FOR FLAMMABLE LIQUIDS CLASS IC.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR XYLENE,IF IN
EXCESS OF TLV.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN