

BOSTIK DIVISION, USM CORP.,EMHART INDUSTRIES INC. -- BOSTIK 1007,ADHESIVE PRIMER --
8040-00-598-5164

===== Product Identification =====

Product ID:BOSTIK 1007,ADHESIVE PRIMER

MSDS Date:01/01/1987

FSC:8040

NIIN:00-598-5164

MSDS Number: BFHGH

=== Responsible Party ===

Company Name:BOSTIK DIVISION, USM CORP.,EMHART INDUSTRIES INC.

Address:BOSTON ST

City:MIDDLETON

State:MA

ZIP:01949

Country:US

CAGE:E

O452

=== Contractor Identification ===

Company Name:BOSTIK DIVISION, USM CORPORATION

CAGE:EO452

Company Name:USM CORP SUB OF EMHART INDUSTRIES INC BOSTIK DIV

Address:BOSTON ST

Box:City:MIDDLETON

State:MA

ZIP:01949

Country:US

Phone:508-777-0100

CAGE:70707

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 22.0%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LB

S

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 34.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 8.0%

OSHA

PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 4.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES,THROAT:CAUSES
HEADACHE,NAUSEA,DIZZ & NORCOSIS BY HI-EXPOSURES

=====
===== First Aid Measures =====

First Aid:INHALATION;REMOVE TO FRE

SH AIR.GET MED ATTN.GIVE ARTIFICIAL
RESP IF NEEDED;EYES:FLUSH W LG AMT OF WATER FOR AT LEAST 15 MIN.GET
MED ATTN:SKIN:WIPE OFF IMMEDIATELY.WASH W/SOAP AND H*2O.FLUSH
W/WATER.GE T MD IF NEEDED.

===== Fire Fighting Measures =====

Flash Point:20F SCC
Lower Limits:1.1
Upper Limits:10.0
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:MFR RECOMMENDS TO USE AIR MASK;
Unusual Fire/Explosion Hazard:NONE NOTED BY MFR.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SURCES OF IGNITION.PROVIDE
VENTILATION.AVOID BREATHING VAP.USE APPROPRIATE PROTECTIVE
EQIPMENTS.COVER W/EXTINGUISHER FOAM.SCRAPE UP W/PLASTIC
SCRAPER;DIKE LG QTY OF SPILL W/COMMERCIAL AB SORBING MATL.PUMP LIQ
TO SALVAGE TANK.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A DRY,COOL PLACE (APPROX
60-80F)AWAY FROM SUNLIGHT,OTH
ER SOURCES OF HEAT/IGNITION.KEEP
CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.
Other Precautions:USE W/ADEQUATE VENTILATION.AVOID SKIN CONTACT.AVOID
PROLONGED OR REPEATED BREATHING VAP.USE IN SPARKS/FLAME-FREE AREA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF CONTAINED BREATHING APPARATUS IN POOR
VENTILATED AREA
Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACEPTABLE.
Protective Gloves:PLASTIC
Eye Protection:SAFETY GLASSES
Other Protective Equipment:SAFETY SHOWER & EYE BATH
Supplemental Safety and Health
6TH INRED:CARBON TETRACHLORIDE,CAS #56-23-3,TLV:10PPM,WT %:0.88-SUSP
CARCINOGEN; MSDS DATED 8/7/84,CONFORMS TO NEW OSHA STDS;VAP OR:55.9
AT 20C;SEE PNI:A THIS NSN FOR OLD FORMULATION

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:171-293F
Vapor Pres:56
Vapor Density:3.07
Spec Gravity:0.948
Evaporation Rate & Reference:3.7(ETHYL ETHR=1)
Solubility in

Water:SLIGHT

Appearance and Odor:BROWN COLORED LIQ WITH AN ESTER ODOR.

Percent Volatiles by Volume:88%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID IGNITION SOURCES

Hazardous Decomposition Products:CO,CO*2,HCL GAS, & OTHER TOXIC FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &

DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.