

PRATT AND LAMBERT INC -- 741-034 -- 8010-00-598-5460

=====  
Product Identification  
=====

Product ID:741-034  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-598-5460  
MSDS Number: BFHHC  
=== Responsible Party ===  
Company Name:PRATT AND LAMBERT INC  
Address:945 BURLINGTON  
Box:206  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
Emergency Phone Num:316-733-1361  
CAGE:92216  
=== Contractor Identification ===  
Company Name:PRATT AND LAMBERT INC  
Address:945 BURLINGTON  
Box:206  
City:KANSAS CITY  
State:MO  
ZIP:64141  
Country:US  
CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingredient Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 35.0%  
OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALED-ANESTHETIC, IRRITATE AIRWAY; SKIN/EYE  
IRRITATION HEADACHE, DIZZINESS, COMA, CONFUSION

=====  
First Aid Measures  
=====

First Aid:INCASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR, CALL A PHYSICIAN IF SYMPTONS PERSISTS. PERFORM ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED.

=====  
Fire Fighting Measures  
=====

Flash Point:104 F, 40 C TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL; POLYMER

FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMENNED

Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY CAUSE EXPLOSION. USE WATER TO COOL CANS; FOR FIRE:FOGNOZZLES

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INE RT ABSORBENT AND NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY, CONTAINERS SHOULD BE GROUNDED WHEN POURING, AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT FLAME CUT, BRAZE, OR WELD COATED MATERIAL WITHOUT VENTI LATION.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/ PROPER FILTER OR HOOD.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health  
BOILING RANGE 155-189 C

=====  
Physical/Chemical Prop  
=====

erties =====

HCC:F4

Boiling Pt:B.P. Text:311-3730.F

Evaporation Rate & Reference:< ETHER

Appearance and Odor:BROWN POINT

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES, HEAT, & HOT SURFACES, SPARKS,  
ELECTRICAL EQUIPMENT

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND

FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.