

NORRIS PAINT COMPANY -- TT-P-29J, GREEN, 34300, LATEX FLAT WALL PAINT -- 8010-00-598-5724

=====  
Product Identification  
=====

Product ID: TT-P-29J, GREEN, 34300, LATEX FLAT WALL PAINT

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00-598-5724

MSDS Number: BFHHV

=== Responsible Party ===

Company Name: NORRIS PAINT COMPANY

Emergency Phone Num: (503) 364-2277

CAGE: JO883

=== Contractor Identification ===

Company Name: NORRI

S PAINT CO., DIV WHITTAKER COATINGS

Address: 1675 COMMERCIAL ST NE

Box: 2023

City: SALEM

State: OR

ZIP: 97308

Country: US

Phone: 503-364-2277

CAGE: 33148

Company Name: NORRIS PAINT COMPANY

Box: 2023

CAGE: JO883

=====  
Composition/Information on Ingredients  
=====

Ingred Name: VINYL ACETATE (SARA III)

CAS: 108-05-4

RTECS #: AK0875000

Fraction by Wt: 25.0%

OSHA PEL: 10 PPM/15 STEL

ACGIH TLV: 10 PPM/15, A3 STEL; 93

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

Ingred Name: ETHYLENE GLYCOL (SARA III)

CAS:107-21-1  
RTECS #:KW2975000  
Fraction by Wt: 1.8%  
OSHA PEL:C 50 PPM  
ACGIH TLV:C 50 PPM,VAPOR; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 2.3%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT OTHERWISE REGULATED)  
CAS:1302-76-7  
RTECS #:BD1450000  
Fraction by Wt: 35.3%  
OSHA PEL:15 MG/M3 TOTAL DUST  
ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:PHENYL MERCURIC ACETATE (SARA III)  
CAS:62-38-4  
RTECS #:OV6475000  
Fraction by Wt: 0.1%  
OSHA PEL:0.1 MG HG/M3;CEIL;S  
ACGIH TLV:0.01 MG HG/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

==== Hazards Identification =====

Effects of Overexposure:WAPORMAY BE IRRIT TO EYES,SKIN,MAY CAUSE SYMPTOMS OF HEADACHE,NAUSEA IN POORLY VENTIL AREAS.

==== First Aid Measures =====

First Aid:SKIN CONTACT:WASH THOROUGHLY W/SOAP & WATER. EYE

S:FLUSH

W/PLENTY OF WATER FOR 15 MIN. CALL PHYSICIAN. IF EXPOSED TO LARGE AMOUNTS OF SPRAY MIST REMOVE TO FRESH AIR. INGEST:INDUCE VOMITING. CALL MD.

=====  
Fire Fighting Measures  
=====

Flash Point:NON FLAMMABLE

Fire Fighting Procedures:N/A ACCD TO MFR

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABSORB SPILL, FLUSH W/LARGE AMOUNTS OF WATER IMMED. TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL.

DO NOT FLUSH  
DOWN SEWER SYSTEM.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP MATERIAL FROM FREEZING

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR WHEN SPRAYING PAINT

Ventilation:ADEQUATE VENTILATION

Protective Gloves:NOT NEC REQD

Eye Protection:SPLASH PROOF SAFETY GOG

Other Protective Equipment:EYE WASH EQUIPMENT.

Supplemental Safety and Health

ADDI  
TIONAL INGREDIENTS: WATER,33.6%;CELLULOSE, 0.5%; SURFACTANTS, 1.4%

=====  
Physical/Chemical Properties  
=====

HCC:N1

Boiling Pt:B.P. Text:212F

Vapor Density:>1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:50

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

OIL & OIL BASE MATERIALS,PETROLEUM DISTILLATES,STRONG ACIDS

Stability Condition to Avoid:EXTREME HEAT OVER 200F

==

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM DISPOSE IN LANDFILL IAW FED, STATE &  
LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this do

cument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.