

NAZ DAR COMPANY -- SCREEN WASH, 2555 -- 6810-00-598-6600

=====
===== Product Identification =====

Product ID:SCREEN WASH, 2555

MSDS Date:01/01/1985

FSC:6810

NIIN:00-598-6600

MSDS Number: BFHMC

=== Responsible Party ===

Company Name:NAZ DAR COMPANY

Address:1087 N NORTH BRANCH ST

City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

CAGE:DO971

=== Contractor Identification ===

Company Name:NAZ DAR COMPANY

Addr

ess:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4234

Country:US

CAGE:DO971

Company Name:NAZDAR COMPANY

Address:1087 N NORTH BRANCH ST

Box:City:CHICAGO

State:IL

ZIP:60622-4292

Country:US

Phone:312-943-8338;800-736-7636

CAGE:76708

=====
===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 100%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT

Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:SKIN & EYE: PRIMARY IRRIT. INHAL: ANESTHETIC.
(SEE SUPP DATA)

=====
First Aid Measures
=====

First Aid:EYES: IMMED FLUSH W/ WATER FOR 15 MIN, SEE MD. SKIN: WASH W/
SOAP & WATER. REMOVE CONTAMINATED CLOTHES. INHAL: REMOVE FROM
EXPOS. RESTORE BREATH. KEEP WARM & QUIET. CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:80F; 26.7C (TCC)

Lower Limits:1.0

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER SPRAY MAY BE
INEFFECTIVE

Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CANS, USE FOG
NOZZLES.

Unusual Fire/Explosion Hazard:CLOSED CANS MAY AUTOIGNITE OR EXPLODE
WHEN EXPOS TO EXTREME HEAT. KEEP FROM HEAT IGNITION SOURCES.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. AVOID BREATH
VAP
ORS. VENTILATE AREA. REMOVE SPILL W/ INERT ABSORBENT AND
NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F; 49C. STORE
LARGE QUANTITIES IN BLDGS DESIGNED FLAMMABLE LIQUIDS.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQ IN EXCESS OF A FEW INCHES. DO NOT TAKE INTERNALLY.
DO NOT FLAME CUT,BRAZE OR WELD W/O APPRVD RESPIRATOR OR ADEQUATE
VENT.

==

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR RECOMNDS NIOSH/MSHA APPRVD RESPIRATOR FOR PARTICULAR EXPOSURE.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST SUFFICIENT TO KEEP BELOW TLV.

Protective Gloves:RECOMMENDED

Eye Protection:EYEWEAR FOR SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT W/ CONTAMINATED CLOTH.

Supplemental Safety and Health

OVEREXPOSURE: IRRIT OF RESP TRACT OR ACUTE NERVOUS SYS DEPRESN MARKED BY HDCH,

DIZZ, STAGGERING GAIT, CONT-USN, UNCON, OR COMA. CONTAINER SIZE: NO SIZE INFO AVAILABLE.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:281-284F

Vapor Pres:6.0

Vapor Density:>1

Spec Gravity:0.87

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR LIQUID

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avo

id:YES

Hazardous Decomposition Products:THERMAL: HAZARDOUS FUMES WHICH MAY CONTAIN CO & OXIDES OF N

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS DO NOT INCINERATE CLOSED CONTAINERS. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of

America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.