

KALCOR COATINGS -- TPO-910, LAMOBBLACK, 1D -- 8010-00-598-7325

=====  
Product Identification  
=====

Product ID:TPO-910, LAMOBBLACK, 1D

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-7325

MSDS Number: BFHNC

=== Responsible Party ===

Company Name:KALCOR COATINGS

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

CAGE:DO396

=== Contractor Identification ===

Company Name:KALCOR COATI

NG CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

Company Name:KALCOR COATINGS COMPANY

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094

Phone:800-424-9300 CHEMTREC

CAGE:DO396

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LINSEED OIL

CAS:8001-26-1

RTECS #:OI9690000

Fraction by Wt: 59.9%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by

Wt: 12.0%  
OSHA PEL:100 PPM

Ingred Name:ADDITIVES  
Fraction by Wt: 1.7%

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Fraction by Wt: 25.0%  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:TURPENTINE  
CAS:8006-64-2  
RTECS #:YO8400000  
Fraction by Wt: 1.4%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM; 9192

=====  
Hazards Identification =====

Effects of Overexposure:SKIN/EYE IRRIT

=====  
First Aid Measures =====

First  
Aid:IF SPLASHED, FLUSH AREA W/WATER

=====  
Fire Fighting Measures =====

Flash Point:105F  
Extinguishing Media:CO\*2, FOAM, DRY CHEM  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures =====

Spill Release Procedures:USE DISPOSABLE ABSORBENT

=====  
Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESS HEAT, OPEN FLAME, SPARKS

=====

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHST

Protective Gloves:REC

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:NONE

Supplemental Safety and Health

VAP DNSTY HEAVIER THAN AIR. % VOLATILE: 15.9. WT/GAL=8.7 LB/GAL.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:315-385F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:15.9

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:EPA APPRVD LANDFILL OR INCINERATION

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.