View NSN Online: https://aerobasegroup.ae/nsn/8010-00-616-7689

Product ID:742426 ENAMEL ALKYD GLOSS GREEN 14158 MSDS Date:01/01/1987 FSC:8010 NIIN:00-616-7689 **MSDS Number: BFHZS** === Responsible Party === Company Name: PRATT AND LAMBERT INC Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Info Phone Num:316-733-1361 Em ergency Phone Num:716-873-6000 DOT EMER 8002553924 CAGE:61196 === Contractor Identification === Company Name: PRATT AND LAMBERT INC Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:*MINERAL SPIRITS CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100PPM

Ingred Name

:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:IRON OXIDE CAS:1332-37-2 RTECS #:NO7380000

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192

Effects of Overexposure:SWALLOW:GASTROINTESTINALIRRIT, NAUSEA,VOMIT,DIARRHEA.MATRL INTO LUNGS CA N CAUS FATAL PNEUMONITIS

First Aid:IF SWALLOW:INDUCE VOMITING IMMED BY GIVING 2 GLASSES OF WATR& STICKING FINGR DOWN THROAT.CONSULT DR OR POISON CONTROL CENTR IMMED. (NEVER GIVE ANYTHING BY MOUTH AN UNCONSCIOUS PERSON) INHAL:REMOV TO F RESH AIR IMMEDIATELY.

Flash Point:80F 27C

Extinguishing Media:CL B FIRES:CO*2, DRY CHEMICAL OR ALCOH FOAM. Fir

e Fighting Procedures:SELF-CONTND BREATHING APPARAT. WATR TO COOL EXPOS CONTNRS

Unusual Fire/Explosion Hazard:CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & FLAME.MAY EXPLOD IF EXPOS TO EXTREME HEAT.

Spill Release Procedures: KEEP SPECTATORS AWAYELIMINATE ALL IGNITION SOURCES (FLAMES, HOT SURFACES, & SOURCES OF ELECTRICAL, STATIC OR FRICTIONAL SPARKS). DIKE & CONTAIN SPILL W/INERT MATRL(E.G. SAND, EARTH).TRANSFR LIQDS TO COVE R METAL CONTNR F/RECOVRY OR DISPOSAL,REMOV W/INERT

Handling and Storage Precautions:DO NOT STORE ABOV 120F.STORE LG QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.105.
Other Precautions:DO NOT TAKE INTERNALLY.CLOS CONTNR AFTER USE. EMPTY CONTNRS MUST NOT BE WASHED & RE-USED F/ANY PURPOSE.CONTNRS MUST BE GROUNDED & BONDED TO RECEIVING CONTNR.DO NOT WELD,BRAZE,CUT ON EMPTY CONT

====

====== Exposure Controls/Personal Protection ==========

Ventilation:LOC EXHAUST VENTILAT TO REMOV DECOMPOSITION BY PRODUCTS. Protective Gloves:SOLVNT IMPERMEA Eye Protection:SAFETY SPECTACLES AT ALL Other Protective Equipment:NOT LIKELY TO BE NEEDED. Supplemental Safety and Health *INDICATES SOLVENT. HAZ. DECOMP.PRODUCTS: IN ADDIT, OXIDES OF LEAD MAY

BE GENERATED.

HCC:F3 Boiling Pt:B.P. Text:193-395F Vapor Densit y:HEAV Evaporation Rate & amp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:60

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS. Hazardous Decomposition Products:BURNING,HEAT BY WELDING,CUTTING WILL PROD SMOK,CO & CO*2.(SU

Waste Disposal Methods:DISPOSE IN ACCORD W/FED. STATE & LOC LAWS.CONTAM ABSORBANT MAY BE D

ISPOS IN EPA-PERMITTED HAZARDOUS WASTE LANDFILLS. INCINERATE ONLY INEPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.OBSER V PRECAUTIONS F/FLAMMABLE MATERIAL DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its u

se. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.