View NSN Online: https://aerobasegroup.ae/nsn/7510-00-616-9588

Product ID:AEROSOL CLEANING SOLVENT, GP-00OT-0620 MSDS Date:01/01/1987 FSC:7510 NIIN:00-616-9588 MSDS Number: BFJDD === Responsible Party === Company Name: SEYMOUR/SYCAMORE, IL 60178 Emergency Phone Num: (815) 895-9101 CAGE:LO703 === Contractor Identification === Company Name:SEYMOUR OF SYCAMORE Address:917 CROSBY AVE. Box:City:SYCAMORE State:IL ZIP:60178-1343 Country:US Phone:815-895-9101/800-255-3924 CAGE:59581 Company Name:SEYMOUR/SYCAMORE, IL 60178 CAGE:LO703

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 75% OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

Ingred Name:PROP ANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 15% OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192

Ingred Name:ISOBUTANE CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 10% ACGIH TLV:1000 PPM

Effects of Overexposure:DIZZINESS/NAUSEA/HEADACHE/LOSS OF COORDINATION/EQUILBRIUM/UNCONSCIOUSNESS/EVEN DEATH.

. SKIN CONTACT: WASH OFF IN FLOWING WATER/SHOWER. REMOVE CONTAMINATED CLOTHING/WASH BEFORE RE-USE. INHALATION: REMOVE TO FRESH AIR. IF DIFFICULT, GIVE OXYGEN . INGESTION: DON'T INDUCE VOMITING. GETMED ATT.

Flash Point:NONE Lower Limits:1.90 Extinguishing Media:CO2, DRY CHEMICAL, FOAM Fire Fighting Procedures:WATER TO COOL CONTAINERS TO PREVENT BURSTING. WEAR SCBA. Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CAN.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION, AVOID BREATHING VAPORS, VENTILATE AREA. WIPE UP WITHNERT MATERIALS AND PLACE IN APPROPRIATE CONTAINER.

Handling and Storage Precautions:DON'T STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.
Other Precautions:USE ONLY
AS DIRECTED. INTENTIAL MISUSE BY
DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE HARMFUL OR FATAL.

Respiratory Protection:AVOID CONTINOUS BREATHING OF VAPORS/SPRAY MIST. SCBA >TLV LIMITS. Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV. Protective Gloves:OPTIONAL Eye Protection:GOGGLES Supplemental Safety and Health MSDS DATE: 06 OCT 1986.

========= Physical/Chemical Proper

HCC:V3 Vapor Density:>AIR Evaporation Rate & amp; Reference:FASTER THAN ETHER Percent Volatiles by Volume:85%

Stability Indicator/Materials to Avoid:YES METALLIC ALLUMINUM AND ZINC POWDERS. Stability Condition to Avoid:DON'T STORE >120F. KEEP FROM SPARKS/PILOT LIGHT/OPE N FLAME. Hazardous Decomposition Products:FUMES MAY CONTAIN CO/OXIDES OF NITROGEN AND PHOSGENE.

====== Disposa

Waste Disposal Methods:DON'T INCINERATE AEROSOL, DIPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DON'T PLACE AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate a nd

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.