

AMERICAN WRITING INK CO, INC -- O-T-620,TYPE 3 -- 8010-00-616-9588

=====
Product Identification
=====

Product ID:O-T-620,TYPE 3

MSDS Date:01/01/1985

FSC:8010

NIIN:00-616-9588

MSDS Number: BFJDG

=== Responsible Party ===

Company Name:AMERICAN WRITING INK CO, INC

Emergency Phone Num:617-482-9167

CAGE:82956

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT S

TREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 94.5%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

=====
Hazards Identification
=====

Effects

of Overexposure: ANESTH EFFECTS, SKIN/EYE IRRIT, CARDIAC IRRIT

=====
First Aid Measures
=====

First Aid: FLUSH SKIN/EYES W/WATER. ARTIF RESP, REMOVE TO FRESH AIR.
INGEST: INDUCE VOMIT, CALL MD.

=====
Fire Fighting Measures
=====

Lower Limits: 8.0
Upper Limits: 10.5
Extinguishing Media: WATER-FOG
Fire Fighting Procedures: SELF-CNTND RESP APPARATUS
Unusual Fire/Explosion Hazard: NONE

=====
Accidental Release Measures
=====

Spill Release Procedures: USE PROPER PROT EQUIP. MOP UP IMMED. REMOVE TO
OUTDOORS. LG SPILLS: EVACUATE AREA, CONTAIN LIQ & TRANSFER TO
CLOSED METAL CNTNRS. KEEP OUT OF WATER SUPPLY.

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE IN DRY, COOL AREA

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: USE SELF-CNTND BRTHNG APPARATUS
Ventilation: GEN OR LOCAL
Eye Protection: GLASSES
Other Protective Equipment: EYEWASH STATIONS/SAFETY SHOWERS READILY
AVAILABLE
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC: T4
Boiling Pt: B.P. Text: 165F, 74C
Vapor Pres: 100
Vapor Density: 4.55
Spec Gravity: 1.319
Solubility in Water: NEGLIGIBLE
Appearance and Odor: COLORLESS LIQ
Percent Volatiles by Volume: 100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YE

S

AVOID WATER

Stability Condition to Avoid: OPEN FLAMES, HI-TEMP AREAS

Hazardous Decomposition Products: EVOLUTION OF HYDROGEN CHLORIDE FROM
THERMAL DEGRADATION

===== Disposal Considerations =====

Waste Disposal Methods: SEND SOLVENT TO RECLAIMER

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.