

SILMAR DIV/VISTRON CORP -- SILMAR S-517C -- 8040-00-633-8373

=====
Product Identification
=====

Product ID:SILMAR S-517C

MSDS Date:01/01/1985

FSC:8040

NIIN:00-633-8373

MSDS Number: BFJNV

=== Responsible Party ===

Company Name:SILMAR DIV/VISTRON CORP

Address:12335 S VAN NESS AVE

City:HAWTHORNE

State:CA

ZIP:90250-3320

Country:US

CAGE:KO579

=== Contractor Identification ===

Company Name:SILMAR DIV V

ISTRON CORP

Address:12335 S VAN NESS AVE

Box:City:HAWTHORNE

State:CA

ZIP:90250-3320

Country:US

CAGE:3H920

Company Name:SILMAR DIV/VISTRON CORP

Address:12335 S VAN NESS AVE

Box:City:HAWTHORNE

State:CA

ZIP:90250-3320

Country:US

CAGE:KO579

=====
Composition/Information on Ingredients
=====

Ingred Name:UNSATURATED POLYESTER

Fraction by Wt: 67%

Ingred Name:STYRENE MONOMER

CAS:57-11-4

RTECS #:WI2800000

Fraction by Wt: 29%

ACGIH TLV:100PPM (MFR)

Ingred Name:PHOSPHONATE ESTER

Fract

ion by Wt: 4%

=====
Hazards Identification
=====

Effects of Overexposure:INHAL:IRRIT TO ALL PARTS RESP
TRACT.EYE:EXTREMELY IRRIT.SKIN:MODERATE IRRIT.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR,GIVE ARTIF RESP IF NEEDED.SKIN:WASH
W/SOAP & WATER,REMOVE CONTAMINATED CLOTH.EYE:FLUSH W/WATER 15
MIN,HOLD EYELID AWAY FROM EYEBALL SEE MD.INGEST:SEE MD IMMED.

=====
Fire Fighti
ng Measures
=====

Flash Point:87F/30C (TCC)

Lower Limits:1.1

Upper Limits:6.1

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL

Fire Fighting Procedures:FIGHT LIKE A FUEL OIL FIRE

Unusual Fire/Explosion Hazard:MONOMERS WILL REACDILY POLYMERIZE AT ELEV
TEMPS.CLOSED CONTAINERS MAY RUPTURE VIOLENTLY

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.AVOID DIRECT
SKIN CONTACT AND INHALATION OF VAP
ORS.USE ABSORBENT MATERIALS LIKE
PERLITE AND VERMICULITE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND
SUNLIGHT.MAINTAIN ADEQUATE SEPARATION FROM CATALYSTS AND PROMOTERS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IAW EXPOSURE OF
CONCERN

Ventilation:LOCAL

Protective Gloves:SOLVENT RESIST

Eye Protection:CHEM SAFETY GOGGLES

Supplemental Safety and Health

MFR MAKES SEVERAL RESINS WHICH CONFORM TO MIL-R-7575 WHICH IS PART OF
PRODUCTS LISTED IN MIL-R-21607. TYPE: GRADE 1. PKG 1 GAL

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:145C/293F

Vapor Pres: