

PRODUCTS TECHNIQUES INC -- PT-107 -- 5970-00-647-3676

===== Product Identification =====

Product ID:PT-107

MSDS Date:01/01/1985

FSC:5970

NIIN:00-647-3676

MSDS Number: BFJWS

=== Responsible Party ===

Company Name:PRODUCTS TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

City:RIALTO

State:CA

ZIP:92316

Country:US

Emergency Phone Num:NONE

CAGE:IO636

=== Contractor Identification ===

Company Name:PRODUCTS T

ECHNIQUES INC

Address:3271 SO RIVERSIDE AVE

Box:City:RIALTO

State:CA

ZIP:92316

Country:US

Phone:714-887-3951;213-770-3600

CAGE:IO636

Company Name:PRODUCTS/TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

Box:City:RIALTO

State:CA

ZIP:92376

Country:US

Phone:909-877-3951

CAGE:06341

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 41.6%

OSHA PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- IS

OMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 3.62%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:RESIN
Fraction by Wt: 51.3%

Ingred Name:SALICYLANILIDE
CAS:87-17-2
RTECS #:VN7850000
Fraction by Wt: 3.45%
ACGIH TLV:500 PPM

===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA,MODERATELY IRRITATING TO EYES &
SKIN

===== First Aid Measures =====

First Aid:REMOVE VICTIM FROM VAPORS,RESTORE BREATHING IF
NECESSARY.REMOVE FROM SKIN WITH SOAP & WATER. FLUSH EYES WITH
PLENTY OF WATER

===== Fire Fighting Measures =====

Flash Point:82F-TCC
Lower Limits:1.1
Upper Limits:7.0
Extinguishing Media:CARBON DIOXIDE,FOAM, OR DRY CHEMICAL
Fire Fighting Procedures:DO NOT USE WATER
Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIVE MIXTURE BETWEEN
UPPER &LOWER EXPLOSIVE LIMITS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION,APPLY SAWDUST OR
OTHER ABSORBENT MATERIAL.KEEP MATERIAL FROM SPREADING

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE-STORE AWAY FROM OPEN FLAME
AND HIGH HEAT.
Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED SKIN CONTACT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CONFINED AREAS USE BUREAU OF MINES
RESPIRATORY DEVICE
Ventilation:LOCAL TO KEEP BELOW LOWER EXPLOSIVE LIMIT
Protective Gloves:YES
Eye Protection:YES
Other Protective Equipment:RUBBER SOLES.BM2304 CARTRIDGE,BM23-12
FILTERS,BM23-13 CUPS
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:225-300F
Vapor Density:>1.0
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor
:LIQUID
Percent Volatiles by Volume:52.7

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS
Hazardous Decomposition Products:CO,CO*2,ALDEHYDES AND OTHER ORGANICS

===== Disposal Considerations =====

Waste Disposal Methods:PUT IN METAL CONTAINER AND SEAL FOR DISPOSAL

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of
the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.