View NSN Online: https://aerobasegroup.ae/nsn/6505-00-664-0329

Product ID:FORMALDEHYDE MSDS Date:01/20/1988 FSC:6505 NIIN:00-664-0329 MSDS Number: BFKJL === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Address: PARIS BYPASS Box:M City:PARIS State:KY ZIP:40361 Info Phone Num:314-982-5000 Emergency Phone Num:314-982 -5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910

Ingred Name:FORMALDEHYDE (SARA III) CAS:50-00-0 RTECS #:LP8925000 Fraction by Wt: 37.0% Other REC Limits:NONE OSHA PEL:SEE 1910.1048 ACGIH TLV:C 0.3 PPM; A2; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:ME

THYL ALCOHOL (METHANOL) (SARA III) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 10-15% Other REC Limits:NONE OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:WATER, WT% BY DIFFERENCE CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 48-53%

LD50 LC50 Mixture:LD50 ORAL RAT=800MG/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP :YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: ACUTE: SEE SIGNS & SYMPTOMS OF OVEREXPOSURE. CHRONIC: HYPERSENSITIVITY LEADING TO CONTACT DERMATITIS, ALLERGIC REACTION, VISION IMPAIRMENT, ENLARGEMENT OF LIVER Explanation of Carcinogenicity: FORMALDEHYDE IS A SUSPECTED HUMAN CARCINOGEN. Effects of Overexposure: EYES: IRRITATION, REDNESS, PAINS, BLURRED VISION, IRREVERSIBLE EYE DAMAGE;SKIN:REDNESS,PAIN,BURNS,DISCOLORATION,CRACKING,SCALING;SKIN ABSORPTION: SAME SYMPTOMS AS INGESTION; INHALATION: SORE THROAT.COUGH.SHOR TNESS OF BREATH.IRRITATION.SEVERE RESPIRATORY TRACT INJURY LEADING TO PULMONARY EDEMA & PNEUMONITIS-SEE SUPPLEMENTAL DAT Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS, OR IMPAIRED LIVER, KIDNEY OR RESPIRATORY FUNCTION.

First Aid:EYES:WASH WITH PLENTY OF WATER FOR 15 MINUTES.SEE DOCTOR IMMEDIATELY;SKIN:FLUSH WITH PLENT

Y OF WATER FOR 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING & SHOES;INHALATION:REMOVE TO FRESH AIR.GIVE CPR /OXYGEN IF NEEDED.SEE DOCTOR;INGESTION:GIVE 2 GLASSES OF WATER.INDUCE VOMIT.NOTHING BY MOUTH IF UNCONSCIOUS.SEE DOCTOR IMMEDIATELY.

Flash Point:140F(60C) Autoignition Temp:Autoignition Temp Text:572F Lower Limits:7.0 Upper Limits:73 Extinguishing Media:WATER SPRAY CAN BE USED TO EXTINGUISH FIRES & COO L

FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR SCBA & PROTECTIVE CLOTHING. WATER MAY BE USED TO FLUSH SPILLS & TO DILUTE SPILLS TO NON-FLAMMABLE MIXTURES. Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIMITS; AUTO IGN TEMP:300C(572F)

Spill Release Procedures:WEAR SCBA & PROTECTIVE CLOTHING.REMOVE IGNITION SOURCES.VENTILATE.ABSORB IN INERT MATERIAL & PL ACE IN

APPROPRIATE DISPOSAL CONTAINER.

 Handling and Storage Precautions:KEEP CONTAINERS CLOSED.PROTECT AGAINST PHYSICAL DAMAGE.OUTSIDE OR DETACHED STORAGE IS PREFERRED.INSIDE STORAGE SHOULD BE IN STD FLAMM.LIQ.STORAGE ROOM
Other Precautions:SEPARATE FROM OXIDIZING MATERIALS.STORAGE & USE AREAS SHOULD BE NO SMOKING.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR A SUPPLIED AIR,FULL-FACEPIECE RESPIRATOR,AIRLINED HOOD,OR SCBA IF TLV IS EXCEEDED. Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:IMPERVIOUS PROTECTIVE CLOTHING,INCLUDING BOOTS,LAB COAT,APRON OR COVERALLS. SAFETY SHOWER & EYE WASH STATION. Work Hygienic Practices:WASH HANDS,FACE,FOREARMS & NECK WHEN EXITING RESTRICTED AREAS-SEE SUPPLEMENTAL DATA. Supplemental Safety and Health CONT'D FROM SIGNS & SYMPTOMS OF OVEREXPOSURE:MAY BE FATAL IN HIGH CONCENTRATIONS;INGESTION:SEVERE ABDOMINAL PAIN,VIOLENT VOMIT,HEADACHE,DIARRHEA.DECREASED BODY TEMPERATURE,PAIN IN DIGESTIVE TRACT,SHAL LOW RESPIRATION,WEAK IRREGULAR PULSE,UNCONSCIOUSNESS,DEATH.METHANOL COMPONENT AFFECTS OPTIC NERVE & MAY CAUSE BLINDNESS.

HCC:F4 Boiling Pt:B.P. Text:205F(96C) Melt/Freeze Pt:M.P/F.P Text:5F(-15C) Vapor Density:1.04 Spec Gravity:1.08 Solubility in Water:COMPLETE Appearance and Odor:CLEAR,COLORLESS LIQUID. PUNGENT ODOR.

Stability Indicator/Materials to Avoid:YES OXIDIZERS,ALKALIES,PERCHLORIC ACID,NITROGEN DIOXIDE,NITROMETHANE,HYDROCHLORIC ACID. Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CO

Waste Disposal Methods:COLLECT SPILLS & A TOMIZE IN A RCRA-APPROVED

COMBUSTION CHAMBER.BEFORE ATOMIZING, DISSOLVE IN AN APPROPRIATE COMBUSTIBLE SOLVENT.WASTE CAN BE DISPOSED IN A RCRA APPROVED FACILITY.ENSURE COMPLIANCE W/LOC AL, STATE & FED REGS: CWA/CERCL RQ:1000 LBS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informati on to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.