

CON-LUX MOATINGS,INC. -- ENAMEL,ALKYD GLOSS 17875 -- 8010-00-664-4761

=====
Product Identification
=====

Product ID:ENAMEL,ALKYD GLOSS 17875

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-4761

MSDS Number: BFKPM

=== Responsible Party ===

Company Name:CON-LUX MOATINGS,INC.

Emergency Phone Num:201-287-4000

CAGE:LO239

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADG

E RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

Company Name:CON-LUX MOATINGS,INC.

Box:847

CAGE:LO239

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40.2%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF EYES AND SKIN.IRRITATION OF
RESPIRATORY TRACT.HEADA

CHE OR DIZZINESS.

=====
First Aid Measures
=====

First Aid:SKIN/EYE:FLUSH W/PLENTY OF WATER.INHAL:MOVE TO FRESH AIR. IF IRRITATION PERSISTS,CONSULT A DR.

=====
Fire Fighting Measures
=====

Flash Point:40.6/105 TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CLASS B EXTINGUISHERS (CO*2,DRY CHEM.OR FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT AUTOIGNITION.

Unusual Fire/Expl

losion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND ISOLATE FROM SOURCES OF IGNITION.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING OF VAPORS.VENTILATE AREA.REMOVE WITH NON-SPARKING TOOLS AND INERT ABSORBENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP

AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM./MECH FILTER RESPIRATOR.

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GOGGLES OR GLASSES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTACT

MINATED CLOTHING.

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:157.2/315

Vapor Pres:1

Vapor Density:4.7

Spec Gravity:1.1

Evaporation Rate & Reference:BUAC=1: 0.15

Solubility in Water:0

Appearance and Odor:WHITE LIQUID,MILD ALIPHATIC ODOR.

Percent Volatiles by Volume:60

===== Stability and Reactivity Dat

a =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.