

UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA -- AMSCO SOLV 1005 * REGULAR MINERAL SPIRITS -- 6850-00-664-5685

=====
===== Product Identification =====

Product ID:AMSCO SOLV 1005 * REGULAR MINERAL SPIRITS

MSDS Date:06/16/1987

FSC:6850

NIIN:00-664-5685

MSDS Number: BFKQL

=== Responsible Party ===

Company Name:UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA

Address:1345 N MEACHAM

City:SCHAUMBURG

State:IL

Z

IP:60196

Info Phone Num:312-490-2500

Emergency Phone Num:312-490-2500

CAGE:94684

=== Contractor Identification ===

Company Name:PHIPPS PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

Company Name:UNOCAL CHEMICALS DIV.,UNION OIL OF CALIFORNIA

Address:1345 N MEACHAM

Box:City:SCHAUMBURG

State:IL

ZIP:60196

Phone:312-490-2500/800-424-9300(CHEMTREC)

CAGE:94684

=====
===== Composition/Information on Ingredients =====

=====
Ingred Name:PETROLEUM NAPHTHA (MINERAL SPIRITS) MFR IDENTIFIES PRODUCT AS THIS. ALSO LISTS INGREDIENT 02 WITHOUT PERCENTAGE.

CAS:64741-41-9

Fraction by Wt: 100%

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT

IS IRRITATING TO EYES AND

MUCOUS MEMBRANES. PROLONGED-REPEATED EXPOSURE MAY LEAD TO PAINTER'S SYNDROME. DELIBERATELY CONCENTRATING AND INHALING THIS PRODUCT MAY BE HARMFUL OR FATAL.

Effects of Overexposure:EYE:IRRITATION,BURNING,TEARING. SKIN:PROLONGED EXPOSURE CAUSES DRYING,CRACKING. INHALED:RESPIRATORY IRRITATION,CENTRAL NERVOUS SYSTEM DEPRESSION,DROWSINESS,DIZZINESS,LOSS OF CO-ORDINATION,FATIGUE. INGESTED:G/I IRRITATION,CENTRAL NERVOUS SYSTEM DEPRESSION,DROWSINESS,DIZZINESS,ETC.

Medical Cond Aggravated by Exposure:ASTHMA & SIMILAR RESPIRATORY DISEASES.

=====
First Aid Measures
=====

First Aid:EYE/SKIN:FLUSH WITH WATER.IF IRRITATION PERSISTS,CALL A PHYSICIAN. INHALED:REMOVE FROM EXPOSURE. IF BREATHING DIFFICULTY;GIVE OXYGEN AND GET MEDICAL ATTENTION. INGESTED:DO NOT INDUCE VOMITING. GET IMM EDIATE MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Poi

nt Method:TCC

Flash Point:101F/39C

Lower Limits:0.7

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS. BEWARE OF SPREADING BURNING LIQUID WITH THE COOLING WATER.

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION AND VENTILATE AREA. KEEP OUT OF DRAINS ,SEWERS OR WATERWAYS. ABSORB ON INERT MATERIAL. STORE IN TIGHTLY CLOSED CONTAINERS PENDING DISPOSAL.

Neutralizing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL,DRY,WELL VENTILATED AREA,FREE FROM IGNITION SOURCES. DO NOT CUT,WELD,GRIND,ETC.,ON CONTAINERS.

Other Precautions:EMPTY CONTAINERS MAY CONTAIN RESIDUE OR VAPORS. EXPLOSION HAZARD. TREAT WITH DUE RESPECT.

=====
Exposu

re Controls/Personal Protection =====

Respiratory Protection:USE NIOSH RESPIRATOR FOR ORGANIC VAPORS OR SUPPLIED AIR RESPIRATOR IF EXPOSED OVER TLV.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURES BELOW TLV.

Protective Gloves:IMPERMEABLE

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER/EYE WASH. IMPERVIOUS CLOTHING IS RECOMMENDED FOR OPERATIONS WHERE SPLASHING AND CONTACT ARE ROUTINE.

Work Hygienic Practices:USE NORMAL CHEMICAL HYGIENE PRACTICE.

Supplemental Safety and Health

MSDS DATED 23JULY86,#6299.EFFECTS:GI IRRITATION,DROWNING,DIZZINESS,COORDINATION LOSS,FATIGUE,ASPIRATION POSSIBLE.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:310-405F

Vapor Pres:3.1 MM@20C

Vapor Density:4.9 (AIR)

Spec Gravity:0.788

Evaporation Rate & Reference:0.12 (BUAC)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR,ALMOST COLORLESS LIQUID,HYDROCARBON ODOR

Percent Volatiles by Volume:100

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS,STRONG BASES,OXIDIZING AGENTS,SELECTED AMINES

Stability Condition to Avoid:HEAT,IGNITION SOURCES

Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS. HMIS SUGGESTS INCINERATION.

Disclaimer (provided with this information by the co

mpiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.