View NSN Online: https://aerobasegroup.ae/nsn/6750-00-680-7877

Product ID:194 7738, STOP BATH, PROCESS C-22 MSDS Date:01/01/1985 FSC:6750 NIIN:00-680-7877 Kit Part:Y **MSDS Number: BFLHR** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name: ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 72.5% **OSHA PEL:10 PPM** ACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS

Ing

DOT Rpt Qty:5000 LBS

red Name:AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED(25-30%) Fraction by Wt: 27.5%
======================================
Effects of Overexposure:SKIN/EYES:DIRECT CONTACT W/LIQUID CAUSES IRRITATION.VAPOR IRRITATING.
======================================
First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FO R 15 MIN.GET MED ATTN IF IRRITATION DEVELO PS.
======================================
 Flash Point:NONE Extinguishing Media:CO*2,DRY CHEM Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY. Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE OR EXPLOSION HAZARD.
======================================
Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTECTV CLOTHNG/SAFETY GLASSES.STOP LEAK W/O RISK.PROVIDE VENT.DIKE LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONT;MFGR RECOMMENDS, FLUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAWS
Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions: AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE &

WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF PRODUCT:3.5

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.
Ventilation:MECHANICAL(GEN) RECOMMENDED BY MFR & LOCAL EXH IF NECESSARY.
Protective Gloves:IMPERVIOUS/RUBR
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.
Supplemental Safety and Health
KEY 1: PO1; MSDS FM MFR DTD: 4/28/76; ITEM HAS 5 PARTS
(BLEACH, DEVELOPER, FIXER, HARDENER A & B, & STOP BATH); THIS IS STOP BATH

IN GLASS BOTTLE; SEE OTHER PNI THIS NSN FOR OTHER PARTS. KEY 1: C1

HCC:F6 Boiling Pt:B.P. Text:>212F/>100C Vapor Pres:32 Vapor Density:1.16 Spec Gravity:1.12 Solubility in Water:COMPLETE Appearance and Odor:CLEAR LIQUID,VINEGAR ODOR. Percent Volatiles by Volume:96%

Stability Indicator/Materials to Avoid:YES STRONG ALKALIS;FLAMM/OXIDIZING MATL. Stability Condition to Avoid:UNK Hazardous Decomposition Products:CO,CO*2 BY THERMAL DECOMPOSITION.

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP WASTE MATL TO DISPOSL FACILITY IAW DOT/EPA REGS.HANDLE/DISPOSE IN FULL COMPLIANCE W/ALL INTNL,FED,STATE/LOCAL REGS;MFGR RECOMMENDS,FLUSH TO SEWER W/LG AMT OF WATER IAW FED,ST ATE/LOCAL EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informatio n to their

particular situation.