

OCTAGON PROCESS INC. -- ASTM D-3487-76/82A,TYPE I/II;ELECT INSU OIL -- 9160-00-685-0913
===== Product Identification =====

Product ID:ASTM D-3487-76/82A,TYPE I/II;ELECT INSU OIL

MSDS Date:01/01/1987

FSC:9160

NIIN:00-685-0913

MSDS Number: BFLNS

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596-RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945

-9400

Emergency Phone Num:201-945-9400

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:MIXED PETROLEUM HYDROCARBONS (NOT SPECIFIED BY THE
SUPPLIER)

Other REC Limits:5MG/CUM AS OIL MIST

OSHA PEL:NOT KNOWN

ACGIH TLV:NOT KNOWN

Ingred Name:PER MSDS,THIS PRODUCT DOES NOT CONTAIN ANY

PCBS
RTECS #:9999999ZZ

=====
Hazards Identification
=====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:SKIN,EYES AND RESPIRATORY
IRRITATION FROM OIL MIST OR VAPORS. CHRONIC:IRRITATION OR POSSIBLE
DERMATITIS.
Effects of Overexposure:PROLONGED OR REPEATED CONTACT MAY CAUSE MILD
SKIN IRRITATION.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH WITH WATER.SKIN:WASH WITH SOAP AND WATER.INGEST:DO
NOT INDUCE VOMITING-CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:320F/160C COC
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:DO NOT MIX WITH OR STORE NEAR STRONG
OXIDANTS LIKE LIQUID CHLO
RINE OR CONC OXYGEN.

=====
Accidental Release Measures
=====

Spill Release Procedures:RECOVER FREE LIQUID,ABSORB WITH
SAWDUST,EARTH,ETC.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.STORE AWAY FROM
HEAT,IGNITION SOURCES,STRONG OXIDANTS.
Other Precautions:AVOID BREATHING OIL MIST,LAUNDRER OIL SOAKED CLOTHING
BEFORE RE-USE,DISCARD OIL SOAKED SHOES.

=====
Exposure Cont

rols/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL OR USE SCBA IN CONFINED AREA.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:RUBBER,CORR RES

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST.DO NOT CONTAMINATE CLOTHES;WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

MSDS UNDATED;LETTER RECEIVED FROM OCTAGON DATED JANUARY 24,1989.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:550F/288C

Vapor Pres:0.01

Vapor Density:8.9

Spec Gravity:0.878

Evaporation Rate & Reference:0.01 (BUT ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT COLORED LIQUID, SLIGHT PETROLEUM ODOR

Percent Volatiles by Volume:NEGLIG

===== Stability and Rea
ctivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:CO*2,CO,UNBURNED HYDROCARBONS,SO*2

===== Disposal Considerations =====

Waste Disposal Methods:APPROVED DISPOSAL SITE I/AW FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of

Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.