

GOAL CHEMICAL SEALANTS CORP -- GC-408 CLASS A -- 8030-00-723-5343

=====
Product Identification
=====

Product ID:GC-408 CLASS A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-723-5343

MSDS Number: BFMLV

=== Responsible Party ===

Company Name:GOAL CHEMICAL SEALANTS CORP

Address:3137 E 26TH ST

City:LOS ANGELES

State:CA

ZIP:90023-4206

Country:US

CAGE:04011

=== Contractor Identification ===

Company Name:GOAL C

HEMICAL SEALANTS CORP

Address:3137 E 26TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90023-4206

Country:US

Phone:213-269-0461

CAGE:04011

=====
Composition/Information on Ingredients
=====

Ingred Name:MANGANESE DIOXIDE (AS MANGANESE)

CAS:1313-13-9

RTECS #:OP0350000

Fraction by Wt: 52.1%

OSHA PEL:C,5 MG/M3/1 FUME TWA

ACGIH TLV:5 MG/M3 DUST/1 FUME

Ingred Name:P-TERPHENYL(TERPHENYL-PLASTICIZER)

CAS:92-94-4

RTECS #:WZ6475000

Fraction by Wt: 38.5%

ACGIH TLV:1 PPM

Ingred Name:GUANIDINE,

1,3-DIPHENYL(DIPHENYL GUANIDINE)

CAS:102-06-7

RTECS #:MF0875000

Fraction by Wt: 9.4%

=====
Hazards Identification
=====

Effects of Overexposure:EYE,SKIN:IRRITATION;INHALE:DIZZINESS DUE TO TOLUENE IN BASE COMPOUND(WHEN MIXING,OR USING).

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR;SKIN,EYES:FLUSH WITH LARGE AMOUNTS OF WATER;INGESTION:ADMINISTER EMETIC.CALL PHYSICIAN. NOTE:WASH SKIN AFTER EACH USE WITH SOAP AND WATER.

=====
Fire Fighting Measures
=====

Flash Point:77F,25C OC

Extinguishing Media:H2O,CO2,DRY CHEM.

Fire Fighting Procedures:NONE NOTED BY MFG(IF LG FIRE, SUGGEST SELF-CNTND BRTHG APP)

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIM IGNITION SOURCES.STOP LEAK.SCRAPE UP EXCESS MATERIAL,AND CLEAN UP RESIDUE W SOLVENTS(FOLLOW APPROPRIATE

HANDLING PROCEDURES FOR SOLVENTS).MIXED PRODUCT IS LIQUID CEMENT,OR SYNTHETIC RUBBER, & CON SIDERED NON HAZARDOUS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL(50 TO 80F),DRY,VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:SEE DATA UNDER PN IND A, THIS STOCK NUMBER.(TWO PART PRODUCT).

=====
Exposure Controls/Personna
=====

I Protection =====

Respiratory Protection:GAS MASK W CANSTR FOR ORGANIC SOLVENTS,NIOSH APPR.

Ventilation:LOCAL EXHAUST ADEQUATE TO ELIMINATE ODOR.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES.

Other Protective Equipment:AS REQUIRED;NORMAL WORK CLOTHING GENERALLY ADEQUATE.

Supplemental Safety and Health

PART B OF TWO PART PRODUCT(CATALYST INGREDIENTS FOR SYNTHETIC RUBBER SEALING COMPOUND).TYPE II,CLASS A-2.SEE DATA SHEETS FOR PART A FOR MORE DATA.KEY1:

J1.

===== Physical/Chemical Properties =====

HCC:F4

Spec Gravity:1.47

Appearance and Odor:BLACK;MERCAPTAN ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG REDUCING AGENTS.

Stability Condition to Avoid:AVOID ELEVATED TEMPERATURES(ABOVE 400F).

Hazardous Decomposition Products:SO₂,H₂S,AND OTHER SULFUR COMPOUNDS

===== Disposal Considerations =====

Waste Disposa

I Methods:CONSIDERED BY MFG TO BE NON-HAZARDOUS TRASH(WHEN MIXED);DISPOSE IN FULL REGULATORY COMPLIANCE.IF CATALYST NOT MIXED,THE PLASTICIZER SHOULD BE NOTED FOR DISPOSAL COMPLIANCE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for i

ts use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.