View NSN Online: https://aerobasegroup.ae/nsn/8010-00-753-4550 ENMAR AN AMERON CO -- GREEN 14050;742-404;ENAMEL ALKYD GLOSS -- 8010-00-753-4550 Product ID:GREEN 14050;742-404;ENAMEL ALKYD GLOSS MSDS Date:01/01/1987 FSC:8010 NIIN:00-753-4550 MSDS Number: BFMYS === Responsible Party === Company Name: ENMAR AN AMERON CO Address: 201 N BERRY ST City:BREA State:CA ZIP:92621-3904 Country:US CAGE:JO877 === Contractor Identification = Company Name: AMERON INDUSTRIAL COATINGS DIVISION Address: 201 N BERRY ST Box:City:BREA State:CA ZIP:92621-3904 Country:US Phone:714-529-4597 CAGE:09869 Company Name: ENMAR AN AMERON COMPANY CAGE:JO877 Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000

======= Composition/Information on Ingredients ========

Fraction by Wt: 49.6% OSHA PEL:100 PPM

Effects of Overexposure: INH: ANESTHE

| TIC, IRRIT OF RESP TRACT OR ACUTE CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYES: IRRIT |
|---|
| ====================================== |
| First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSCIAN IF SYMPTOMS PERSIST. |
| ====================================== |
| Flash Point:104F TCC Lower Limits:1.1 Extinguishing Media:SM FIRES:CO*2, DRY CHEM. LG FIRES:POLYMER FOAM PREFERRED Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE W/INERT ABSRBENT & NON-SPARKING TOOLS. |
| ==== ================================= |
| Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ DO NOT TAKE INTERNALLY. ADD LABEL WARNING.J Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF LIC IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTLATION. DOT: FLAM LIQUID |
| ====== Exposure Controls/Personal Protection ========= |
| Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUME Protective Gloves:YES Eye Protection:YES FOR SPLASH Other Protective Equipment:AVOID LONG EXPOSURE TO CONTA CLOTHING Supplemental Safety and Health VAPOR PRESSURE: 3.2; VAPOR DENSITY: HEAVIER THAN AIR; WT PER GALLON: 8.3 LBS |
| ========= Physical/Chemical Properties ========== |
| HCC:F4 Boiling Pt:B.P. |

| Percent Volatiles by Volume:63.5 |
|---|
| ======== Stability and Reactivity Data ========= |
| Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES |
| ======= Disposal Considerations ========== |

Evaporation Rate & Evaporation R

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this inform ation by the compiling agencies):

Text:311-373F

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.