View NSN Online: https://aerobasegroup.ae/nsn/6850-00-753-4827

U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND -- DECONTAMINATING AGENT DS2 -- 6850-00-753-4827

Product ID: DECONTAMINATING AGENT DS2 MSDS Date:09/28/1984 FSC:6850 NIIN:00-753-4827 **MSDS Number: BFNDS** === Responsible Party === Company Name: U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND Address:ATTN: SMCCR-SFS. HDQ, BLDG E5101 **City:ABERDEEN PROVING GROUND** State: MD ZIP:21010-5423 Country:US Info Phone Num:301-278-5201 (AFTER DUTY HOURS) Emergency Phone Num:301-671-4411 (0800-1630 EST) CAGE:80706 === Contractor Identification === Company Name: ASTRO DEVELOPMENT LABORATORY INC Address:236 CALIFORNIA ST Box:City:EL SEGUNDO State:CA ZIP:90245-4309 Country:US CAGE:7K997 Company Name: POLY RESEARCH CORPORATION Address:125 CORPORATE DRIVE Box:City:HOLTSVILLE State:NY ZIP:11742-2007 Country:US Phone:516-758-0460 CAGE:64713 **Company Name: TIMMERMAN** CAGE:TIMMR Compan

y Name:U.S. ARMY ARMAMENT, MUNITIONS & CHEMICAL COMMAND Address:ATTN: SMCCR-SFS. HDQ, BLDG E5101 Box:City:ABERDEEN PROVING GROUND State:MD ZIP:21010-5423 Country:US Phone:301-671-4411 (0800-1630 EST) CAGE:80706 Company Name:WRIGHT CHEMICAL CORP Address:ACME STATION Box:City:RIEGELWOOD State:NC ZIP:28456 Country:US CAGE:5U648

Ingred Name:DIETHYLENE TRIAMINE CAS:111-40-0 RTECS #:IE1225000 Fraction by Wt: 69.-71%. OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III) CAS:109-86-4 RTECS #:KL5775000 Fraction by Wt: 27.-29%. OSHA PEL:S, 25 PPM ACGIH TLV:S, 5 PPM; 9192

Ingred Name:SODIUM HYDROXIDE (SARA III) CAS:1310-73-2 RTECS #:WB4900000 Fraction by Wt: 1.9-2.1% OSHA PEL:2 MG/M3 ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:MATERIAL MANUFACTURED FOR ARMY IAW THE REQMTS OF SPEC.; ARMY'S CHEM. RES. & DEV. CTR. PROVIDED THE MASTER MSDS. RTECS #:9999 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CORROSIVE TO TISSUE & HIGHLY
IRRITANT TO RESPIRATORY TRACT; CHRONIC: REPEATED EXPOSURE TO
"DETA" CAN CAUSE SKIN SENSITIZATION & ASTHMA; SUFFICIENT EXPOSURE
TO "EGME" MAY CAUSE "CNS" DEPRESSION & LIVER DAMAGE. ALTHOUGH NOT
DEFINITELY ESTABLISHED IN HUMANS,
REPRODUCTIVE EFFECTS ARE ALSO A
MAJOR CONCERN.
Effects of Overexposure:NO TOX. DATA AVAILABLE ON DS2. HOWEVER, DS2:
ALKALI WHICH ON CONTACT WILL CORRODE TISSUE. EFFECTS EXHIBITED ARE
A FUNCTION OF ROUTE OF EXPOS., AMT. OF SUBST. PRESENT & DURATION OF

EXPOSURE; HEALTH EFF ECTS RANGE FROM MILD BURNS & PRIMARY IRRITATION TO CORNEAL OPACIFICATION, SEVERE BURNS, NAUSEA, VOMITING(SEE SUPPL DATA)

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY CONDITIONS.

====

First Aid:SKIN: FLUSH AWAY W/WATER UNTIL "SOAPINESS" IS NO LONGER PRESENT; EYES: IMMEDIATELY FLUSH W/COPIOUS AMTS. OF WATER FOR AT LEAST 15 MINS. IN EITHER CASE, SEEK MEDICAL ATTN.; INHAL: REMOVE TO FRESH AIR - GIVE CPR/O*2 AS SITUATION DICTATES. ADDITIONAL SUPPORTIVE MEASURES MAY BE REQUIRED; INGEST: IF CONSCIOUS, GIVE PATIENT AS MUCH MILK OR WATER AS POSSIBLE. DO NOT INDUCE VOMITING. GET MED. ATTN. IMMED.

Flash Point:168F,76C Extinguishing Media:CARBON DIOXIDE, ALCOHOL FOAM, WATER Fire Fighting Procedures:NONE CITED Unusual Fire/Explosion Hazard:NEVER MIX OR STORE WITH ACIDS, OXIDIZING AGENT OR STB (UPER TROPICAL BLEACH); FIRE OR EXPLOSION MAY RESULT.

Spill Release Procedures: SPILLS ON POROUS SURFACES (CONCRETE, WOOD, ETC.) SHOULD BE CLEANED & NEUTRA

LIZED IMMEDIATELY. OTHERWISE, IT WILL BE ABSORBED & BECOME AN INDEFINITE HAZARD. CONTAIN SPILL, NEUTRALIZE, ABSORB ON VERMICUL ITE, CLAY OR DIATOMACEOUS EARTH. SCOOP UP IN DRUM! Neutralizing Agent:SODIUM BISULFATE Handling and Storage Precautions: AVOID EXTREME TEMPERATURES(I.E. 160F/71C) FOR STORAGE! AVOID CONTACT W/LEAKING LIQUID OR VAPOR. Other Precautions: SPILL/RELEASE PROCEDURE CONTD: SCOOP UP MATERIAL & CONTAMIN. MATTER, PLACE IN EPOXY COATED DRUM W/REMOVABLE HEAD IAW EPA & DOT RQMTS.; DURING CLEAN-UP, WEAR FULL FACE RESPIR. W/ORGANIC VAPOR CARTRIDGE, ARM-LENGTH RUBBER GLOVES & RUBBER APRON. Respiratory Protection: FOR DS2 AIRBORNE CONC. 5 PPM OR EMERGENCIES, USE "SCBA" Ventilation: LOCAL EXHAUST: NECESSARY IF TLV(TWA) EXCEEDED. Protective Gloves: BUTYL RUBBER: ARM'S LENGTH TYPE Eve Protection: SPLASHPROOF GOGGLES /FULL F ACE SHIELD Other Protective Equipment: AS REQUIRED FOR TASK AT HAND; CORROSIVE RESISTANT(I.E. RUBBER) GAUNTLET, BOOTS, & APRON Work Hygienic Practices: USE MATERIAL IAW THE GUIDELINES & INSTRUCTIONS SET FORTH IN USER'S TECH MANUAL. Supplemental Safety and Health SIGNS & SYMPTOM OVEREXP. CONTD: RESPIRATORY IRRITATION, SKIN SENSITIZATION. HCC:B1 Boiling Pt:B.P. Text:380F,193C Spec Gravity: 0.97 - 0.98 pH:>12.5 Appearan ce and Odor: CLEAR AMBER SOLUTION WITH AMMONIA-LIKE ODOR Stability Indicator/Materials to Avoid:YES CORROSIVE. INCOMPATIBLE WITH AL, CD, ZN, PAINT, WOOL, OXIDIZING MATERIALS. Stability Condition to Avoid: EXPOSURE TO AIR, DS2 WILL DETERIORATE IN AIR. EXPOSURE OF 48 HOURS OR MORE TO OPEN AIR PRODUCES GELATIN-LIKE BODIES. Hazardous Decomposition Products:NONE CITED

======= Disposal Considerations ======

Waste Disposal Methods:CHOICE OF METHOD DEPENDS ON PHYSICAL CONDITION OF WASTE & FACILITY'S CAPABILITY.FOR EXCESS STOCK,COORDINATE W/LOCAL DRMO;OVERSEAS:OPERATE W/IN HOST COUNTRY & DRMO REGS.; WASTE CORROSIVE(PH >12.5) W/EP A HAZ. NO:D002; INCINERATE OR NEUTRALIZE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoe ver,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.