

STERLING,DIVISION REICHOLD CHEMICALS,INC -- 80-122(BEFORE MARCH 1977) --  
5970-00-755-9003

===== Product Identification =====

Product ID:80-122(BEFORE MARCH 1977)

MSDS Date:01/01/1985

FSC:5970

NIIN:00-755-9003

MSDS Number: BFNPL

=== Responsible Party ===

Company Name:STERLING,DIVISION REICHOLD CHEMICALS,INC

Address:NINE OHIO RIVER BLVD

City:SEWICKLEY

State:PA

ZIP:15143-2199

Country:US

Emergency Pho

ne Num:NONE

CAGE:LO906

=== Contractor Identification ===

Company Name:NU-BRITE CHEMICAL CO INC, STERLING GROUP

Address:NINE OHIO RIVER BLVD

Box:City:SEWICKLEY

State:PA

ZIP:15143-2199

Country:US

Phone:CHEMTREC 800-424-9300

CAGE:78580

Company Name:STERLING,DIVISION REICHOLD CHEMICALS,INC

Address:NINE OHIO RIVER BLVD

Box:City:SEWICKLEY

State:PA

ZIP:15143-2199

Country:US

CAGE:LO906

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III

)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 39.0%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 20.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)  
CAS:111-15-9  
RTECS #:KK8225000  
Fraction by Wt: 4.0%  
OSHA PEL:S,100 PPM  
ACGIH TLV:S, 5 PPM; 9192

=====  
===== Hazards Identification =====

Effects of Overexposure:VAPORS CAUSES IRRITATION OF  
EYES,NOSE,THROAT.HEADACHE,NAUSEA & VOMITING.HIGH  
CONCENTRATIONS,ANESTHET

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR,FLUSH SKIN OR EYES WITH WATER.IF  
DIFFICULTY NOTED IN BREATHING,GET MEDICAL ATTENTION AT ONCE.IF  
SWALLOWED,INDUCE VOMITING & GET MEDICAL ATTENTION AT ONCE

===== Fire Fighting Measures =====

Flash Point:70F TCC  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM,FOG.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH SAWDUST,RAGS,PAPER,OR OTHER  
ABSORBENT SUBSTANCE.REMOVE ALL SOURCES OF IGNITION

===== Handling and Storage =====

Handling and Storage Precautions:

PROTECT AGAINST PHYSICAL DAMAGE. STORE  
IN A WELL VENTILATED, COOL PLACE. SEPARATE FROM OXIDIZING AGENT &  
SOURCES OF IGNITION.

Other Precautions: THE STANDARD FLAMMABLE LIQUIDS STORAGE ROOM SHOULD BE  
USED FOR INDOOR STORAGE. WEAR SAFETY GOGGLES, A CHEMICAL CARTRIDGE  
RESPIRATOR, AVOID PROLONGED OR REPEATED BREATHING OF VAPORS OR SKIN  
CONTACT

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: HIGH CONCENTRATION MAY REQUIRE AIR SUPPLIED MASK  
Ventilation: AS REQUIRED TO CONTROL TLV IN AIR  
Protective Gloves: PLASTIC  
Eye Protection: SAFETY GOGGLES  
Other Protective Equipment: SAFETY SHOWER & EYE WASH  
Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC: F2

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
AVOID OXIDIZING AGENTS.  
Stability Condition to Avoid: WARM STORAGE, IGNITION SOURCES  
Hazardous Decomposition Products: NONE

=====  
===== Disposal Considerations =====

Waste Disposal Methods: SPRAY INTO A FURNACE UNDER APPROVED CONTROLLED  
PROCEDURES. INCINERATION WILL BECOME EASIER BY MIXING WITH A MORE  
FLAMMABLE SOLVENT

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate

and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.