View NSN Online: https://aerobasegroup.com/nsn/9150-00-782-2627

MOBIL OIL CORP -- AVREX S TURBO 256 -- 9150-00-782-2627

Product ID:AVREX S TURBO 256

MSDS Date:06/29/1990

FSC:9150

NIIN:00-782-2627

MSDS Number: BFPGL === Responsible Party ===

Company Name: MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ ZIP:08540 Country:US

Info Phone Num:800-227-0707 X 3265

Emergency Phone Num:609-737-4411/CHEMTREC 800-424-9300

CAGE:6A687

===

Contractor Identification ===

Company Name: MOBIL OIL CORP

Box:1025

City:PRINCETON

State:NJ ZIP:08540 Country:US

Phone:609-737-4411

CAGE:6A687

======= Composition/Information on Ingredients ========

Ingred Name:SYNTHETIC OIL Fraction by Wt: >95.00%

Other REC Limits: NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:TRICRESYLPHOSPHATE

CAS:1330-78-5

RTECS #:TD0175000 Fraction by Wt: 2.33%

Other REC Limits: NONE SPECIFIED

Ingred Name: P, P'-DIOCTYLDIPHENYLA

MINE CAS:101-67-7 RTECS #:JJ8850000 Fraction by Wt: 5,000 MG/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE/CHRONIC-SKIN:PROLONGED REPEATED SKIN CONTACT WITH LOW VISCOSITY MATERIALS MAY DEFAT THE SKIN RESULTING IN POSSIBLE IRRITATION AND DERMATITIS. Effects of Overexposure:SEE HEALTH HAZARDS SECTION. Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN CONDITION MAY GET WORSE.
==== =================================
First Aid:INHALATION:NONE CONSIDERED NECESSARY.EYE:FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN.GET MEDICAL ATTENTION IF IRRITATION PERSISTS.SKIN:WASH WITH SOAP AND WATER.INGESTION:DO NOT INDUCE V OMITING.ADMINISTER VEGETABLE OIL.GET MEDICAL ASSISTANCE.(NOTE TO PHYSICIAN:MATERIAL IF ASPIRATED INTO THE LUNGS MAY CAUSE CHEMICAL PNEUMONITIS.TREAT APPROPRIATELY.)
======================================
Flash Point Method:COC Flash Point:415F,213C Lower Limits:0.6 Upper Limits:7.0 Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING. Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:NONE
======== Accidental Release Measure s ===========
Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC AND SHOVEL UP.REPORT SPILLS AS REQUIRED TO APPROPRIATE AUTHORITIES. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
============ Handling and Storage ==============
Handling and Storage Precautions:STORE IN A COOL DRY PLACE AWAY FROM HEAT AND FLAMES.

Other Precautions: AVOID REPEATED SKIN CONTACT.

Exposure Controls/Personal Protection ========

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS. RESPIRATORY PROTECTION NOT ORDINARILY R EQUIRED.

Ventilation: ROOM VENTILATION IS ADEQUATE.

Protective Gloves: NEOPRENE RUBBER AS REQUIRED.

Eye Protection: SAFETY GLASSES RECOMMENDED.

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

======== Physical/Chemical Properties ===========

HCC:V6
Boiling Pt:B.P. Text:>600F,>316C
Vapor Pres: