

TESTING SYSTEMS,INC. -- FLUORO FINDER FL-2 -- 6850-00-782-2732

=====  
Product Identification  
=====

Product ID:FLUORO FINDER FL-2

MSDS Date:01/01/1985

FSC:6850

NIIN:00-782-2732

MSDS Number: BFPLN

=== Responsible Party ===

Company Name:TESTING SYSTEMS,INC.

Emergency Phone Num:201-767-7300

CAGE:28257

=== Contractor Identification ===

Company Name:TESTING SYSTEMS,INC.

CAGE:28257

=====  
Composi  
tion/Information on Ingredients  
=====

Ingred Name:PIGMENTS

Fraction by Wt: 0.40%

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 90.0%

OSHA PEL:100 PPM

Ingred Name:SULFONAMIDE

CAS:63-74-1

RTECS #:WO8400000

ACGIH TLV:100PPM

Ingred Name:CHLORINATED HYDROCARBONS

Fraction by Wt: 4.0%

ACGIH TLV:200PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:SKIN-DEFATTING

ACTION,IRRITATION,INHALATI

ON-HEADACHE,DROWSINESS,COMP,G.I.IRRIT;VOM  
ITING,DIARRHEA.

=====  
First Aid Measures  
=====

First Aid:SKIN:FLUSH WITH WATER;INHALATION-REMOVE TO FRESH  
AIR,ADMINISTER MOUTH TO MOUTH RESUSCITATION,INGESTION-CONTACT A  
PHYSICIAN;EYES-FLUSH WITH WATER & SEEK MEDICAL ATTENTION

=====  
Fire Fighting Measures  
=====

Flash Point:185F TCC  
Lower Limits:1.0  
Upper Limits:7.5  
Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2  
Fire Fight  
ing Procedures:USE SELF-CONTAINED BREATHING APPARATUS,COOL  
CONTAINERS W/H\*20  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG  
OXIDANTS.COMBUSTIBLE LIQUID

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.RECOVER FREE  
LIQUID W/NON-SPARKING TOOLS.KEEP WELL VENTILATED.ADD ABSORBENT TO  
REMAINING LIQUID.

=====  
Handling and Storage  
=====

Handling and Storage Precaut  
ions:KEEP CONTAINERS CLOSED.KEEP AWAY FROM  
HEAT,SPARKS & OPEN FLAME.AVOID STRONG OXIDIZING AGENTS  
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.REMOVE  
CONTAMINATED CLOTHING.WASH SKIN WITH SOAP & WATER.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:HYDROCARBON VAPOR CANNISTER.  
Ventilation:MECHANICAL,EXPLOSION PROOF,TO KEEP EQUIV.TO OUTDOOR VENTIL.  
Protective Gloves:RUBBER IF REQD  
Eye Protection:PROTECTIVE GOGGLES  
Other Prote

Protective Equipment:HYDROCARBON-INSOLUBLE APRON IF NEEDED  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4  
Boiling Pt:B.P. Text:280F  
Vapor Pres:8.0  
Vapor Density:2.0  
Spec Gravity:0.88  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:YELLOW OILY LIQUID WITH ALIPHATIC ODOR.  
Percent Volatiles by Volume:90+

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:TEMP 600F,DECOMP OF DYE.  
Hazardous Decomposition Products:CO IN CASE OF INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ABSORBED LIQUID ACCORDING TO LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.