View NSN Online: https://aerobasegroup.ae/nsn/8010-00-787-8856

GROW GROUP INC U S PAINT DIV -- MIL-P-38336 -- 8010-00-787-8856

=========== Product Identification =============

Product ID:MIL-P-38336 MSDS Date:01/01/1985

FSC:8010

NIIN:00-787-8856

MSDS Number: BFPVW === Responsible Party ===

Company Name: GROW GROUP INC US PAINT DIV

Address:831 S 21ST ST City:SAINT LOUIS

State:MO

ZIP:63103-3043 Country:US

Info Phone Num:314-621-0525 / FAX 314-621-0722

Emergency Phone Num:314

-621-0525 CAGE:90608

=== Contractor Identification ===

Company Name: US PAINT CORPORATION

Address:831 SOUTH 21ST STREET

Box:City:ST LOUIS

State:MO

ZIP:63103-3092 Country:US

Phone:314-621-0525

CAGE:90608

======= Composition/Information on Ingredients ========

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 24.0% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000 Fraction by Wt: 1 2.0% OSHA PEL:S,200 PPM ACGIH TLV:S, 5 PPM; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS =========== Hazards Identification ========================== Effects of Overexposure: EYE AND UPPER RESPIRATORY IRRITANT First Aid:IF EXPOSED TO EXCESS VAPOR, REMOVE TO FRESH AIR AND SEEK MED. ATT.IF SLASHED ON SKIN OR IN EYES, FLUS W/LG AMT OF WATER & SEEK IMMEDIATE MED ATT.IF INGESTED, DO NOT INDUCE VOMITING BUT SEEK IMMED MEDICA L ATTN. ============ Fire Fighting Measures ========================= Flash Point:45 F TCC Lower Limits: 2.6 Extinguishing Media: DRY CHEMICAL OR FOAM Unusual Fire/Explosion Hazard: DO NOT EXPOSE OR OPEN FLAME ======== Accidental Release Measures ============ Spill Release Procedures: AFFECTED AREA SHOULD BE TREATED WITH AN ABSORBING MATERIAL AND THEN PLACED IN A TIGHTLY CLOSED CONTAINER. ============ Handling and Storage =============== ==== Handling and Storage Precautions: KEEP AWAY FROM EXCESS HEAT, SPARKS, AND FLAME. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: CHARCOAL BASE FOR SOLVENT VAPOR & NIOSH/MSHA **APPROVED** Ventilation: LOCAL EXHAUST-SUFFICIENT TO KEEP AIR SUPPLY BELOW TLV

Other Protective Equipment: HYPERSENSITIVE PERSONS SHOULD WEAR

Protective Gloves: RUBB OR POLYETH

Eye Protection: GOGGLES

PROTECTIVE CREAMS
Supplemental Safety and Health
VAPOR DENSITY IF HEAV

IER THAN AIR.
========== Physical/Chemical Properties ===========
HCC:F2 Boiling Pt:B.P. Text:167 TO 279F Vapor Pres:3. Spec Gravity:1.01 Evaporation Rate & Dr. Reference:1.0 N-BUAC Solubility in Water:APPRECIABLE Appearance and Odor:OFF WHITE-ALCOHOL Percent Volatiles by Volume:39.0
======== Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS Stability Condition to Avoid:EXCESS HEAT Hazardous Decompositio n Products:NONE
======= Disposal Considerations ===========
Waste Disposal Methods: IN ACCORDANCE W/LOCAL STATE & FED CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

ent should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.