

UNION CHEMICALS DIVISION,UNION OIL COMPANY OF CALI -- BLEND 4504;PRODUCT CODE# 4504
-- 6850-00-810-1762

=====
Product Identification
=====

Product ID:BLEND 4504;PRODUCT CODE# 4504

MSDS Date:01/01/1987

FSC:6850

NIIN:00-810-1762

MSDS Number: BFQHW

=== Responsible Party ===

Company Name:UNION CHEMICALS DIVISION,UNION OIL COMPANY OF CALI

Emergency Phone Num:(312)490-2500

CAGE:DO714

=== Contractor Ide

ntification ===

Company Name:UNION CHEMICALS DIVISION

Address:1345 NORTH MEACHAM ROAD

Box:7600

City:SCHAUMBURG

State:IL

ZIP:60196

Phone:213-664-2121 OR 800-424-9300

CAGE:DO714

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

=====
Composition/Information on Ingredients
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
Haza

rds Identification
=====

Effects of Overexposure:EYES:IRRITATION;SKIN:DERMATITIS ON

PROL.CONTACT;INHAL:IRRIT OF RESP.TRACT,LIVER&KIDNEY DAMAGE;CO POI

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;

GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER

SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighti

ng Measures =====

Flash Point:NONE TO BOILING

Extinguishing Media:FOAM,CO*2,DRY CHEMICALS.

Fire Fighting Procedures:USE WATER FOR COOLING; WEAR NIOSH APPROVED
SCBA IN CONFINED

Unusual Fire/Explosion Hazard:BLEND CONTAINING CHLORINATED PRODUCTS MAY
EXHIBIT REDUCED FLASH POINT AS THE MORE VOLATILE CH.EVAPOR

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE
INERT ABSORBENT MATERIAL
AND RECOVER FOR PROPER DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA.AVOID HEAT,OPEN FLAMES;KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH SKIN & EYES;DO NOT BREATHE
VAPORS;WASH THOROUGHLY AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Ey

e Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED:02/24/83:

===== Physical/Chemical Properties =====

HCC:T5

Boiling Pt:B.P. Text:104-180F

Vapor Density:>1.0

Spec Gravity:1.27

Evaporation Rate & Reference: