View NSN Online: https://aerobasegroup.com/nsn/6850-00-823-7861

PYROIL COMPANY, DIV OF CHAMPION LABS, INC -- STARTING FLUID -- 6850-00-823-7861

========= Product Identification ==============

Product ID:STARTING FLUID

MSDS Date:01/01/1987

FSC:6850

NIIN:00-823-7861

MSDS Number: BFQXS === Responsible Party ===

Company Name: PYROIL COMPANY, DIV OF CHAMPION LABS, INC

Address:4TH AND WALNUT ST

City:ALBION State:IL ZIP:62806 Country:US

Emergency Phone Num:NONE KNOWN

CAGE:MO040

=

== Contractor Identification ===

Company Name: CHAMPION LABORATORIES INC

Address:4TH AND WALNUT ST

Box:City:ALBION

State:IL ZIP:62806 Country:US

Phone:618-445-6011

CAGE:1U777

Company Name: PYROIL COMPANY, DIV OF CHAMPION LABS, INC

Address:4TH AND WALNUT ST

City:ALBION

State:IL ZIP:62806 Country:US CAGE:MO040

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ETHER (SARA III)

CAS:60-29-7

RTECS #:KI5775000 Fraction by Wt: 60.0%

OSHA PEL:400 PPM/500 STEL

ACGIH T

Ingred Name: N-HEPTANE CAS:142-82-5 RTECS #:MI7700000 Fraction by Wt: 40.0% OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293 Effects of Overexposure: EYES: IRRITATION, REDNESS, TEARING, BLURRED VISION:SKIN:IRRIT, DEFAT, DERMATITIS:INHAL:DROWSINESS, CNS DEP-First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED; EYES/SKIN: FLUSH W LG AMTS H*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE. ============= Fire Fighting Measures ======================== Flash Point:-36F1-38C (T.C.C Lower Limits: 1.46 Upper Limits:18.6 Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND TO A DISTANT IGNITION SOURCE. ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP FROM HEAT OR FLAME. USE WITH GOOD VENTILATION, AVOID BREATHING VAPOR. Other Precautions: AVOID CONTACT WITH EYES, AND SKIN; DO NOT BREATHE VAPORS. ====== Exposure Controls/Personal Protection ======== Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN

LV:400PPM/500STEL; 9192

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS