View NSN Online: https://aerobasegroup.com/nsn/6850-00-823-7861

## SPRAY PRODUCTS CORPORATION -- FUEL, ENGINE PRIMER TYPE II -- 6850-00-823-7861

Product ID:FUEL, ENGINE PRIMER TYPE II

MSDS Date:01/31/1989

FSC:6850

NIIN:00-823-7861

MSDS Number: BFQXV === Responsible Party ===

Company Name: SPRAY PRODUCTS CORPORATION

Box:737

City:NORRISTOWN

State:PA ZIP:19404 Country:US

Info Phone Num:(215) 277-1010 Emergency Phone Num:(800) 424-9

300 CHEMTREC CAGE:12625

=== Contractor Identification ===

Company Name: SPRAY PRODUCTS CORPORATION

Address: CONSHOHOCKEN RD

Box:737

City:NORRISTOWN

State:PA ZIP:19404 Country:US

Phone:610-277-1010

CAGE:12625

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ETHER (SARA III)

CAS:60-29-7

RTECS #:KI5775000 Fraction by Wt: 60%

OSHA PEL:400 PPM/500 STEL ACGIH TLV:400PPM/500STEL; 9192

EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name: N-HEPTANE

CAS:142-82-5

**RTEC** 

S #:MI7700000 Fraction by Wt: 33%

OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293

Ingred Name: CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000 Fraction by Wt: 6% OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;93

Ingred Name: UPPER CYLINDER LUBRICANT

Fraction by Wt: 1%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:REPEATED AN

D PROLONGED EXPOSURE TO

SOLVENTS MAY CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:INHALATION: MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS. MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION AND IRRITATE MUCOUS MEMBRANES OF THERESPIRATORY TRACT. SKIN: MAY CAUSE DEF ATTING AND DRYING OF THE SKIN.

First Aid: INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED

GIVE ARTIFICIAL RESPIRATION. SKIN: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. EYES: FLUSH WITH WATER FOR 15 MINUTES, IF IRRITATION PERSISTS, CALL PHYSICIAN.INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

========== Fire Fighting Measures ===============

Flash Point Method:TCC Flash Point:-49F/>-44.44C

Lower Limits: 1.85 Upper Limits: 48

Extinguishing Media: FOAM, DRY CHEMICALS, CO2 Fire Fighting Procedures: HANDLE AS EXTREMELY

FLAMMABLE LIQUID, COOL CONTAINERS EXPOSED TO HEAT WITH WATERUSE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS. Unusual Fire/Explosion Hazard: CONTENTS UNDER PRESSURE. ======== Accidental Release Measures ============ Spill Release Procedures: ELIMINATE SOURCES OF HEAT OR IGNITION. VENTILATE AREA. APPLY ABSORBENT MATERIAL TO SPILL AREA. ============= Handling and Storage ========================== Handling and Storage Precautions: EXTREMELY FLAMMABLE. STORE AND USE AWAY FROM ALL HEAT AND IGNITION SOURCES. USE ADEQUATE VENTILA-TION, HAZARDOUS WAST NUMBER U117, D001 Other Precautions: CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120F. DO NOT PUNCTURE OR INCINERATE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR IF VENTILATION IS INADEQUATE. Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) IF REQUIRED. Protective Gloves: NEOPRENE IF SUBJ **ECTED TO EXPOSURE** Eye Protection: CHEMICAL GOGGLES OR SAFETY GLASSES Other Protective Equipment: NONE Work Hygienic Practices: AVOID BREATHING VAPOR AND EYE AND SKIN EXPOSURE. KEEP OUT OF REACH OF CHILDREN. Supplemental Safety and Health NK ========= Physical/Chemical Properties =========== HCC:V3 Boiling Pt:B.P. Text:95F Melt/Freeze Pt:M.P/F.P Text:-177F Vapor Pres:537 Vapor Density:2.55 Spec Gravity:.713 Evaporation Rate & Evaporation R Solubility in Water:SLIGHT Ap

========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE
Stability Condition to Avoid:AVOID OXIDIZERS. KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAMEDO NOT STORE ABOVE 120F
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE MAY BE FORMED DURING COMBUSTION.
======= Disposal Considerations ==========
Waste Disposal Methods: ABSORBING MATERIAL OR DEFECTIVE C

Waste Disposal Methods: ABSORBING MATERIAL OR DEFECTIVE CONTAINERS

pearance and Odor:CLEAR/ETHER SMELL

SHOULD BE DISPOSED AT A RCRA APPROVED TS & D FACILITY AND ACCORDING TO FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profe ssional advice to verify and assume responsibility for the suitability of this information to their particular situation.