

CON-LUX COATINGS,INC. -- ALKYD,FLAT BEIGE 30450 -- 8010-00-823-8012

=====  
Product Identification  
=====

Product ID:ALKYD,FLAT BEIGE 30450

MSDS Date:01/01/1987

FSC:8010

NIIN:00-823-8012

MSDS Number: BFRDF

=== Responsible Party ===

Company Name:CON-LUX COATINGS,INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergency Phone Num:201-287

-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 31%

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 929

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITATION OF EYES AND SKIN.IRRITATION OF  
RESPIRATORY TRACT HEADACHE OR DIZZINESS.

=====  
First Aid Measures  
=====

First Aid:SKIN/EYES:FLUSH W/PLENTY OF WATER. INHAL:MOVE TO FRESH AIR.  
CALL DR.IF IRRITATION PERSISTS.

=====  
Fire Fighting Measures  
=====

Flash Point:128F,53C

Extinguishing Media:USE CLASS B EXTINGUISHERS (  
CARBON DIOXIDE,DRY  
CHEMICAL,FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT  
AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND  
ISOLATE FROM SOURCES OF IGNITION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT  
SURFACES,ELECTOR FRICTIONAL SPARKS,HOT SURFACES)AVOID BREATHING  
VAPORS. VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SP  
ARKING  
TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP  
AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED  
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM/MECH FILTER  
RESPRATOR

Ventilation:LOCAL EXHA

UST  
Protective Gloves: YES  
Eye Protection: SAFETY GLASSES OR GOGGLES  
Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH  
CONTAMINATED CLOTHING.

Supplemental Safety and Health  
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY  
TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC: F4  
Boiling Pt: B.P. Text: 174F, 79C  
Vapor Pres: 4  
Vapor Density: 5.3  
Spec Gravity: 1.37  
Evaporation Rate & Reference: BUAC = 1: 0.05  
Solubility in  
Water: NEGLIGIBLE  
Appearance and Odor: BEIGE LIQUID, MILD ALIPHATIC ODOR.  
Percent Volatiles by Volume: 57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
Hazardous Decomposition Products: CO, CO\*2

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information  
by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.