

SPRAYON PRODUCTS, INC. -- 707 BULK, PDRP, 38212 -- 8030-00-835-4348

=====
Product Identification
=====

Product ID:707 BULK, PDRP, 38212

MSDS Date:01/01/1985

FSC:8030

NIIN:00-835-4348

MSDS Number: BFRVK

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS, INC.

Address:26300 FARGO AVE

City:BEDFORD HEIGHTS

State:OH

ZIP:44146-1310

Country:US

Emergency Phone Num:216-292-7400

CAGE:09800

=== Contrac

tor Identification ===

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 65%

OSHA PEL:100 PPM

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 5%

OSHA PEL:S, 50 PPM

ACGIH

TLV:S, 25 PPM; 9293

=====
Hazards Identification
=====

Effects of Overexposure:INH: RESP IRRITATION, DROWSINESS, NAUS. INGEST:
IRRITATION OF MOUTH,THROAT,STOMACH EYE: IRRITATION

=====
First Aid Measures
=====

First Aid:INH:REMOVE VICTIM TO FRESH AIR, IF BREATH STOP GIVE ARTIF
RESP & O*2 IF NEC,CALL MD. INGEST: DO NOT INDUCE VOMITING. CALL MD
IMMEDIATELY. EYE: WASH THOROUGHLY W/ WATER FOR 15 MINUTES, CALL MD
IMMEDIAT ELY.

=====
Fire Fighting Measures
=====

Flash Point:140F, 60C, TCC
Lower Limits:1.0
Extinguishing Media:CO*2, DRY CHEMICAL OR FOAM.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE WATER TO COOL
EXPOS CONTAINER
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR. MAY MOVE
ALONG FLOOR TO BE IGNITED BY PILOT LIGHT, SPARK OR OTHER FLAME

=====
Accidental Release Measures
=====

Spill Release Procedures:R
EMOVE ALL IGNITION SOURCES. VENTILATE. AVOID
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT. STORE WASTE MATERIAL
IN COVERED,MARKED,METALLIC CONTAINERS AWAY FROM HEAT. DISPOSE AS
SOON AS POSSIBLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL WELL VENTILATED AREA
IN SEALED CONTAINERS. ALL IGNITION SOURCES IN AREA SHOULD BE
CONTROLLED. DO NOT TRANSFER TO UNMARKED CONTAINERS.
Other Precautions:REFER TO 29 C
FR 1910.106 & NFPA NO 30 FOR FLAMMABLE &
COMBUSTIBLE LIQUIDS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR IF REQUIRED.
Ventilation:PROVIDE LOCAL VENTILATION TO KEEP CONC BELOW TLV.
Eye Protection:RECOMMENDED
Supplemental Safety and Health
TYPE II. CONTAINER SIZE - 1 GAL CAN

=====
Physical/Chemical Properties
=====

HCC:V4
Boiling Pt:B.P. Text:360F 182.2C
Vapor Density:> 1
Spec Gravity

:0.829

Evaporation Rate & Reference:< 1 (ETHER = 1)

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS

Hazardous Decomposition Products:CO, CO*2, SO*X, SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS INCINERATION. WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.