

TRIO CHEMICAL WORKS, INC -- MIL-C-23411,CORROSION PREVENTIVE CMPD TY 1 --
8030-00-838-7789

===== Product Identification =====

Product ID:MIL-C-23411,CORROSION PREVENTIVE CMPD TY 1

MSDS Date:01/01/1987

FSC:8030

NIIN:00-838-7789

MSDS Number: BFRZB

=== Responsible Party ===

Company Name:TRIO CHEMICAL WORKS, INC

Address:341-7 SCHOLLES ST

City:BROOKLYN

State:NY

ZIP:11206

Country:US

CAGE:87951

=== Contr

actor Identification ===

Company Name:TRIO CHEMICAL WORKS

Address:341-7 SCHOLLES ST

Box:City:BROOKLYN

State:NY

ZIP:11206

Country:US

CAGE:87951

===== Hazards Identification =====

Effects of Overexposure:INHALATION OF HIGH VAPOR CONCENTRATIONS MAY
RESULT IN MILD DEPRESSION TO CONVULSIONS TO UNCONSCIOUS.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE IMMEDIATELY: CALL PHYSICIAN. IF
SWALLOWED DO NOT IND
UCE VOMITING. IF NEEDED, START RESUSCITATION,
GIVE OXYGEN. REMOVE CONTAMINATED CLOTHING. WASH SKIN W/SOAP &
WATER. FLUSH EYES W /COPIOUS AMTS OF RUNNING WATER.

===== Fire Fighting Measures =====

Flash Point:N/A FOR AEROSOL

Lower Limits:0.90

Upper Limits:6.0

Extinguishing Media:FOAM, DRY CHEMICAL, CO*2, WATER SPRAY

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED
AREAS

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX W/STRONG

OXIDANTS

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. ADD ABSORBENT TO SPILL. AVOID BREATHING VAPORS. VENTILATE ENCLOSURES. DO NOT POUR INTO SEWER.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. KEEP AWAY FROM SPARKS OR OPEN FLAME.

Other Precautions: AVOID PROLONGED INHALATION OF VAPOR OR SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: AIR-SUPPLIED MASK, HYDROCARBON VAPOR CANISTER, OR APPROPRIATE

Ventilation: LOCAL EXH: FACE VELOCITY 60 FPM. MECH: EXPLO PROOF EQUIP ONLY

Protective Gloves: NORM NOT NEEDED

Eye Protection: GOGGLES

Other Protective Equipment: HYDROCARBON INSOLUBLE APRON

Supplemental Safety and Health

FLASH PT. FOR SOLVENT MIXT. = 105 TCC; MFG RECOMMENDS A TLV OF 100 PPM.

===== Physical/Chemical Properties =====

HCC

:V3

Vapor Pres: