

PERMATEX INDUSTRIAL CORP -- FORM-A-GASKET 2, 8008, 2A

=====  
MSDS Safety Information  
=====

FSC: 8030  
NIIN: 00-849-0071  
MSDS Date: 01/01/1991  
MSDS Num: BFSMB  
Product ID: FORM-A-GASKET 2, 8008, 2A  
MFN: 01  
Responsible Party  
Cage: DO527  
Name: PERMATEX INDUSTRIAL CORP  
Address: 30 TOWER LANE  
City: AVON CT 06001  
In  
fo Phone Number: 203-477-7727  
Emergency Phone Number: 203-477-7727  
Preparer's Name: STEPHEN REPETTO  
Proprietary Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: DO527  
Assigned Ind: Y  
Name: PERMATEX INDUSTRIAL CORP; LOCTITE CORP  
Address: 30 TOWER LANE; AVON PARK SOUTH  
Box: 11915  
City: AVON CT 06001

=====  
Cont  
ractor Summary  
=====

Cage: 08028  
Name: LOCTITE CORP AUTOMOTIVE AND CONSUMER GROUP  
Address: 4450 CRANWOOD COURT  
City: CLEVELAND OH 44128-4004  
Phone: 216-663-3011  
Cage: DO527  
Name: PERMATEX INDUSTRIAL CORP; LOCTITE CORP  
Address: 30 TOWER LANE; AVON PARK SOUTH  
Box: 11915  
City: AVON CT 06001  
Phone: 203-677-7727

=====  
Item Description Information  
=====

=  
Item Manager: GSA  
Item Name: SEALING COMPOUND  
Specification Number: MIL-S-45180  
Unit of Issue: TU  
Quantitative Expression: 10000000015OZ  
UI Container Qty: 0

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

=====  
Health Hazards Data  
=====

Signs And Symptions Of Ove

rexposure: CAN ACT AS LOCAL IRRITANT. MFR STATES

PRODUCT IS NOT CONSIDERED AN IMPORTANT TOXIC HAZARD

First Aid: SKIN: WASH THOROUGHLY W/MILD SOAP & WATER AFTER HANDLING. EYES:  
IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN. CALL MD.

=====  
Handling and Disposal  
=====

Spill Release Procedures: MFR SUGGESTS CLEANING UP W/ISOPROPANOL TAKING  
PRECAUTIONS AGAINST POSS FIRE & INH HAZ.

Waste Dispo

sal Methods: HANDLE SM AMTS AS COMBUSTIBLE. LG AMTS, SANITARY  
LANDFILL, MFR SUGGESTIONS. DISPOSE IAW LOCAL, STATE, FED REG.

Handling And Storage Precautions: STORE IN COOL, DRY PLACE NOT OVER 120F

Other Precautions: BP, VAP PRESS, EVAP RATE GIVEN FOR SOLVENT. MFRS CODE: PART  
#2. PROD INSOLUBLE IN WATER WHEN DRIED. VAP PRESS: 31.2MMHG.

=====  
Fire and Explosion Hazard Information  
=====

Flash Po

int Method: TCC

Flash Point Text: 69.0F,20.6C

Lower Limits: 2%

Upper Limits: 12%

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE  
EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE  
=====

Control Measures  
=====

Respiratory Protection: NOT REQ

Ventilation: LOCAL EXHST ADEQUATE

Protective Gloves: NOT REQ

Eye Prot

ection: NOT REQ

=====  
Physical/Chemical Properties  
=====

HCC: V4  
NRC/State LIC No: NA  
B.P. Text: 180F,82C  
Vapor Pres: 33  
Vapor Density: 2.07  
Spec Gravity: 1.50  
Evaporation Rate & Reference: 7.7 (ETHER =1)  
Solubility in Water: PARTIAL  
Appearance and Odor: BLACK PASTE, ALCOHOLIC ODOR  
Percent Volatiles by Volume: 23  
=====

Reactivity Data  
=====

=====  
Stability Indicator: YES  
Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.  
Materials To Avoid: STRONG OXIDIZERS.  
Hazardous Polymerization Indicator: NO  
=====

Toxicological Information  
=====

Ecological Information  
=====

=====  
MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

=====  
Transportation Information  
=====

=====  
Responsible Party Cage: DO527  
Trans ID NO: 88561  
Product ID: FORM-A-GASKET 2, 8008, 2A  
MSDS Prepared Date: 01/01/1991  
Review Date: 06/14/1995  
MFN: 1  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: TU  
Container QTY: 0  
Additional Data: NOT REGULATED FOR SHIPPING  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code: GJJ  
Symbols: G  
DOT Proper Shipping Name: FLAMMABLE  
LIQUIDS, N.O.S.  
Hazard Class: 3  
UN ID Num: UN1993  
DOT Packaging Group: II  
Label: FLAMMABLE LIQUID  
Special Provision: T8,T31  
Non Bulk Pack: 202  
Bulk Pack: 242  
Max Qty Pass: 5L  
Max Qty Cargo: 60 L  
Vessel Stow Req: B  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: HIM  
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o  
IMDG Page Number: 3126  
UN Number: 1993  
UN Hazard Class: 3.1  
IMO Packaging Group: I/II  
Subsidiary Risk Label: -  
EMS Number: 3-07  
MED First Aid Guide NUM: T  
=====

=====  
Detail IATA Information  
=====

IATA PSN BV  
IATA UN ID Num: 1993  
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. \*  
IATA UN Class: 3  
IATA Label: FLAMMABLE LIQUID  
UN Packing Group: II  
Packing Note Passenger: 305  
Max Quant Pass: 5L  
Max Quant Cargo: 60L  
Packaging Note Cargo: 307  
=====

=====  
Detail AFI Information

=====  
AFI PSN BV  
AFI Symbols: \*  
AFI Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.  
AFI Hazard Class: 3  
AFI UN ID NUM: UN1993  
AFI Packing Group: II  
Special Provisions: P5  
Back Pack Reference: A7.3  
=====

HAZCOM Label

=====  
Product ID: FORM-A-GASKET 2, 8008, 2A  
Cage: DO527  
Assigned IND: Y  
Company Name: PERMA  
TEX INDUSTRIAL CORP; LOCTITE CORP  
Street: 30 TOWER LANE; AVON PARK SOUTH  
PO Box: 11915  
City: AVON CT  
Zipcode: 06001  
Health Emergency Phone: 203-477-7727  
Label Required IND: Y  
Date Of Label Review: 05/20/1994  
Status Code: C  
Label Date: 05/20/1994  
Origination Code: G  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: DANGER  
Respiratory Protection IND: YES  
Health Hazard: Moderate  
Contact Hazard: Slight  
Fire Hazard: Severe  
Reactivity Hazard: None  
Hazard And Precautions: ACUTE: MODERATELY  
TOXIC BY INGESTION. VAPOR ABOVE TLV  
IS IRRITATING TO EYES, NOSE AND THROAT AND CAN CAUSE HEADACHE, DIZZINESS,  
NAUSEA. CHRONIC: NONE SPECIFIED BY MANUFACTURER.  
=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to

have any application, use or

viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their parti

cular situation regardless of similarity to a corresponding Department of Defense or other government situation.