

CON-LUX COATINGS, INC -- TT-E-489F,CLASS A -- 8010-00-853-1859

=====
Product Identification
=====

Product ID:TT-E-489F,CLASS A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-853-1859

MSDS Number: BFSTH

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

CAGE:6A064

=== Contractor Identification ===

Company Name:CON-LUX

COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:908-287-4000

CAGE:6A064

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50.8%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:EYE & SKIN: IRRIT. INH: VAPORS-IRRIT RESP
TRACT, CAUSE HEADACHE OR DIZZINESS.

=====

=====
First Aid Measures
=====

First Aid:SKIN & EYE: FLUSH W/PLENTY OF WATER. INHAL: MOVE TO FRESH AIR. IF IRRIT PERSISTS, CONSULT MD.

=====
Fire Fighting Measures
=====

Flash Point:105F TCC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO*2, DRY CHEMICAL, OR FOAM. WATER SPRAY MAY BE INEFFECTIVE.

Fire Fighting Procedures:USE WATER TO COOL CLOSED CANS. KEEP CANS TIGHTLY CLOSED.

Unusual Fire/Explosion Hazard:l

SOLATE FROM IGNITION SOURCES. EXCESSIVE

HEAT MAY EXPLODE CLOSED CANS. DO NOT APPLY TO HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT, NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP AWAY FROM OPEN FLAME, SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY. GROUND CONTANERS WHEN POURING. AVOID PROLONGED, REPEATED CONTACT W/SKIN. DOT: COMBUSTIBLE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:APPROVED CHEM-MECH FILTER RESP

Ventilation:SUFFICIENT TO KEEP TLV BELOW ACCEPTABLE LIMIT

Protective Gloves:YES

Eye Protection:YES, FOR SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT

W/CONTAMINATED CLOTHING
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315F
Vapor Pres:1
Vapor Density:4.70
Spec Gravity:1.0200
Evaporation Rate & Reference:0.15 BUAC
Solubility in Water:NEGLIGIBLE
Appearance and Odor:MILD ALIPHATIC ODOR, BLUE LIQUID
Percent Volatiles by Volume:61.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IAW
FED, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.